

WPRT50AB-470RJB168

WPRT50AB-470RJB168 Information



For Reference Only

Part Number WPRT50AB-470RJB168
Manufacturer TT Electronics/Welwyn

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 470 OHM 5% 50W

Package Radial, Rectangular Case

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WPRT50AB-470RJB168 Specifications

Manufacturer Part Number WPRT50AB-470RJB168 Manufacturer TT Electronics/Welwyn Category Resistors Package Radial, Rectangular Case Series WPRT Resistance 470 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±350ppm/°C Operating Temperature -55°C ~ 155°C Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate - Report errors?		
CategoryResistorsPackageRadial, Rectangular CaseSeriesWPRTResistance470 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 155°CFeaturesAutomotive AEC-Q200, Flame Proof, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension3.543" L x 0.748" W (90.00mm x 19.00mm)Height - Seated (Max)1.299" (33.00mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Manufacturer Part Number	WPRT50AB-470RJB168
Chassis Mount Resistors Package Radial, Rectangular Case WPRT Resistance WPRT Resistance 470 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±350ppm/°C Operating Temperature -55°C ~ 155°C Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Failure Rate -	Manufacturer	TT Electronics/Welwyn
PackageRadial, Rectangular CaseSeriesWPRTResistance470 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 155°CFeaturesAutomotive AEC-Q200, Flame Proof, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension3.543" L x 0.748" W (90.00mm x 19.00mm)Height - Seated (Max)1.299" (33.00mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Category	Resistors
SeriesWPRTResistance470 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 155°CFeaturesAutomotive AEC-Q200, Flame Proof, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension3.543" L x 0.748" W (90.00mm x 19.00mm)Height - Seated (Max)1.299" (33.00mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance470 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 155°CFeaturesAutomotive AEC-Q200, Flame Proof, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension3.543" L x 0.748" W (90.00mm x 19.00mm)Height - Seated (Max)1.299" (33.00mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Package	Radial, Rectangular Case
Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±350ppm/°C Operating Temperature -55°C ~ 155°C Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Series	WPRT
Power (Watts)50WCompositionWirewoundTemperature Coefficient±350ppm/°COperating Temperature-55°C ~ 155°CFeaturesAutomotive AEC-Q200, Flame Proof, SafetyCoating, Housing TypeCeramicMounting FeatureBracketsSize / Dimension3.543" L x 0.748" W (90.00mm x 19.00mm)Height - Seated (Max)1.299" (33.00mm)Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Resistance	470 Ohms
Composition Wirewound Temperature Coefficient ±350ppm/°C Operating Temperature -55°C ~ 155°C Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±350ppm/°C Operating Temperature -55°C ~ 155°C Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Power (Watts)	50W
Operating Temperature -55°C ~ 155°C Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Composition	Wirewound
Features Automotive AEC-Q200, Flame Proof, Safety Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Temperature Coefficient	±350ppm/°C
Coating, Housing Type Ceramic Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Operating Temperature	-55°C ~ 155°C
Mounting Feature Brackets Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Features	Automotive AEC-Q200, Flame Proof, Safety
Size / Dimension 3.543" L x 0.748" W (90.00mm x 19.00mm) Height - Seated (Max) 1.299" (33.00mm) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Coating, Housing Type	Ceramic
Height - Seated (Max) Lead Style Quick Connects, 0.250" (6.35mm) Package / Case Radial, Rectangular Case Failure Rate -	Mounting Feature	Brackets
Lead StyleQuick Connects, 0.250" (6.35mm)Package / CaseRadial, Rectangular CaseFailure Rate-	Size / Dimension	3.543" L x 0.748" W (90.00mm x 19.00mm)
Package / Case Radial, Rectangular Case Failure Rate -	Height - Seated (Max)	1.299" (33.00mm)
Failure Rate -	Lead Style	Quick Connects, 0.250" (6.35mm)
	Package / Case	Radial, Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

WPRT50AB-470RJB168 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WPRT50AB-470RJB168 Payment Methods



















WPRT50AB-470RJB168 Shipping Methods













If you have any question about WPRT50AB-470RJB168, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com