

WSU120-1500 Information



Part Number WSU120-1500 Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 18W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WSU120-1500 Specifications

Manufacturer Part Number WSU120-1500 Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Manufacturer Part Number	WSU120-1500
Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Manufacturer	Triad Magnetics
Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesWSURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.5APower (Watts)18WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Series	WSU
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Region Utilized	North America
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. $x > 5.5\text{mm}$ O.D. $x > 11.0\text{mm}$ Size / Dimension 3.03° L $x > 1.89^{\circ}$ W $x > 1.22^{\circ}$ H (77.0mm $x > 1.0\text{mm}$ x 48.0mm $x > 1.0\text{mm}$)	Form	Wall Mount
Voltage - Output Current - Output (Max) 1.5A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 12V 1.5A 18W No Load Power Consumption 100mW (Max) Positive Center 100mW (Max) Positive Center 100mW (Max) Positive Center 100mW (Max) 100mW (M	Input Type	Fixed Blade
Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 18W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Voltage - Output	12V
No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Current - Output (Max)	1.5A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	Power (Watts)	18W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	No Load Power Consumption	100mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L x }1.89^{\circ}\text{W x }1.22^{\circ}\text{H }(77.0\text{mm x }48.0\text{mm x }31.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Efficiency	Level VI
Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)
		Report errors?

WSU120-1500 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WSU120-1500 Payment Methods



















WSU120-1500 Shipping Methods













If you have any question about WSU120-1500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com