



WSU135-1770-13 Information

Heisener.com

WSU135-1770-13 Part Number Manufacturer Triad Magnetics

Power Supplies - External/Internal (Off-Board) Category

AC DC Desktop, Wall Adapters

Description 100-240V WALL PLUG-IN PWR SUPPLY

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WSU135-1770-13 Specifications

Manufacturer Part Number WSU135-1770-13 Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 1.77A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 13.5 V Current - Output (Max) 1.77 A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Manufacturer Part Number	WSU135-1770-13
Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 1.77A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Manufacturer	Triad Magnetics
Package - WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 13.5V Current - Output (Max) 1.77A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesWSURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output13.5VCurrent - Output (Max)1.77APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 13.5V Current - Output (Max) 1.77A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 13.5V Current - Output (Max) 1.77A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Series	WSU
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 13.5V Current - Output (Max) Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 13.5V Current - Output (Max) 1.77A Power (Watts) No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Form	Wall Mount
Voltage - Output (Max) Current - Output (Max) 1.77A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 13.5V 1.77A 1.00mW (Max) Power (Watts) 100mW (Max) Positive Center 100mW (Max) Positive Center 100mW (Max) Positive Center 100mW (Max) 100m	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.77A 1.	Voltage - Input	90 ~ 264 VAC
Power (Watts) $24W$ No Load Power Consumption $100mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension 3.03 " L x 1.89 " W x 1.22 " H (77.0mm x 48.0 mm x 31.0 mm)	Voltage - Output	13.5V
No Load Power Consumption 100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5 \text{mm}$ O.D. $x 11.0 \text{mm}$ Size / Dimension 3.03 " L $x 1.89$ " W $x 1.22$ " H (77.0 mm $x 48.0 \text{mm}$ $x 31.0 \text{mm}$)	Current - Output (Max)	1.77A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension 3.03 " L x 1.89 " W x 1.22 " H (77.0mm x 48.0 mm x 31.0 mm)	Power (Watts)	24W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	No Load Power Consumption	100mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L x }1.89^{\circ}\text{W x }1.22^{\circ}\text{H }(77.0\text{mm x }48.0\text{mm x }31.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Efficiency	Level VI
Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm
D	Size / Dimension	3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)
Report errors?		Report errors?

WSU135-1770-13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WSU135-1770-13 Payment Methods



















WSU135-1770-13 Shipping Methods













If you have any question about WSU135-1770-13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com