

WSU180-1330-R Information



Part Number WSU180-1330-R Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 18V 24W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WSU180-1330-R Specifications

Manufacturer Part Number WSU180-1330-R Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Manufacturer Part Number	WSU180-1330-R
Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Manufacturer	Triad Magnetics
Package - Series WSU Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesWSURegion UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.33APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Series	WSU
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) Power (Watts) 1.33A Power (Watts) 1.00mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension Fixed Blade 90 ~ 264 VAC	Region Utilized	North America
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{rmm I.D. x 5.5mm O.D. x 11.0mm}$ Size / Dimension $3.03^{\circ}\text{L x 1.89^{\circ}W x 1.22^{\circ}H (77.0mm x 48.0mm x 31.0mm)}$	Form	Wall Mount
Voltage - Output Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 18V 1.33A 1.0mm 100mW (Max) Negative Center 100mW (Max) Negative Center 100mW (Max) Negative Center 100mW (Max) 100mW (Max)	Input Type	Fixed Blade
Current - Output (Max) 1.33A Power (Watts) 1.00mW (Max) No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Voltage - Output	18V
No Load Power Consumption 100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension 3.03 " L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Current - Output (Max)	1.33A
PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension 3.03 " L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Power (Watts)	24W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	No Load Power Consumption	100mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L} \times 1.89^{\circ}\text{W} \times 1.22^{\circ}\text{H} (77.0\text{mm} \times 48.0\text{mm} \times 31.0\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.03^{\circ}\text{L x }1.89^{\circ}\text{W x }1.22^{\circ}\text{H }(77.0\text{mm x }48.0\text{mm x }31.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Efficiency	Level VI
Size / Dimension 3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	3.03" L x 1.89" W x 1.22" H (77.0mm x 48.0mm x 31.0mm)
•		Report errors?

WSU180-1330-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WSU180-1330-R Payment Methods



















WSU180-1330-R Shipping Methods













If you have any question about WSU180-1330-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com