

WSX180-1330-R13

WSX180-1330-R13 Information

Heisener.com	 WSX180-1330-R13 Triad Magnetics Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC WALL MNT ADAPTER 18V 24W - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



WSX180-1330-R13 Specifications

Manufacturer Part NumberWSX180-1330-R13ManufacturerTriad MagneticsCategoryPower Supplies - External/Internal (Off-Board)Ac DC Desktop, Wall AdaptersPackage-SeriesWSXRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output (Max)93APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)Efficiency0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension302" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackageSeriesWSXRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.33APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)Efficiency0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Manufacturer Part Number	WSX180-1330-R13
AC DC bestop, Wall Adapters Package - Series WSX Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Cevel VI Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Manufacturer	Triad Magnetics
Package-SeriesWSXRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.33APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)Efficiency0°C ~ 45°COutput ConnectorBarrel Plug. 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series WSX Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dinension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Series	WSX
Innut TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output90 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.33APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)Efficiency0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Form	Wall Mount
Voltage - Output18VCurrent - Output (Max)1.33APower (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Input Type	Multi-Blade (Included)
Current - Output (Max) 1.33A Power (Watts) 24W No Load Power Consumption 100mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)24WNo Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Voltage - Output	18V
No Load Power Consumption100mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Current - Output (Max)	1.33A
PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Power (Watts)	24W
ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	No Load Power Consumption	100mW (Max)
EfficiencyLevel VIOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Polarization	Negative Center
Operating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Efficiency	Level VI
Size / Dimension 3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)	Operating Temperature	0° C ~ 45°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	3.02" L x 1.87" W x 1.38" H (76.8mm x 47.5mm x 35.0mm)
		Report errors?

WSX180-1330-R13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

WSX180-1330-R13 Payment Methods





If you have any question about WSX180-1330-R13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com