



X0202DA 5BL2 Information



For Reference Only

Part Number X0202DA 5BL2

Manufacturer STMicroelectronics

Category Discrete Semiconductor Products

Thyristors - SCRs

Description SCR 1.25A 400V TO-92

Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









X0202DA 5BL2 Specifications

Manufacturer Part NumberX0202DA 5BL2ManufacturerSTMicroelectronicsCategoryDiscrete Semiconductor ProductsThyristors - SCRsPackageTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Series-Voltage - Off State400VVoltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.45VCurrent - On State (It (AV)) (Max)800mACurrent - On State (It (RMS)) (Max)1.25ACurrent - Hold (Ih) (Max)5mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)22.5A, 25ASCR TypeSensitive GateOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3			
CategoryDiscrete Semiconductor ProductsThyristors - SCRsPackageTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Series-Voltage - Off State400VVoltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.45VCurrent - On State (It (AV)) (Max)800mACurrent - On State (It (RMS)) (Max)1.25ACurrent - Hold (Ih) (Max)5mACurrent - Hold (Ih) (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)22.5A, 25ASCR TypeSensitive GateOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Manufacturer Part Number	X0202DA 5BL2	
Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Series - Voltage - Off State 400V Voltage - Gate Trigger (Vgt) (Max) 800mV Current - Gate Trigger (Igt) (Max) 200μA Voltage - On State (Vtm) (Max) 1.45V Current - On State (It (AV)) (Max) 800mA Current - On State (It (RMS)) (Max) 1.25A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) 5μA Current - Non Rep. Surge 50, 60Hz (Itsm) 22.5A, 25A SCR Type Sensitive Gate Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Manufacturer	STMicroelectronics	
PackageTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Series-Voltage - Off State400VVoltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.45VCurrent - On State (It (AV)) (Max)800mACurrent - On State (It (RMS)) (Max)1.25ACurrent - Hold (Ih) (Max)5mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)22.5A, 25ASCR TypeSensitive GateOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Category	Discrete Semiconductor Products	
Series - Voltage - Off State 400V Voltage - Gate Trigger (Vgt) (Max) 800mV Current - Gate Trigger (Igt) (Max) 200µA Voltage - On State (Vtm) (Max) 1.45V Current - On State (It (AV)) (Max) 800mA Current - On State (It (RMS)) (Max) 1.25A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) 5µA Current - Non Rep. Surge 50, 60Hz (Itsm) 22.5A, 25A SCR Type Sensitive Gate Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3		Thyristors - SCRs	
Voltage - Off State Voltage - Gate Trigger (Vgt) (Max) 800mV Current - Gate Trigger (Igt) (Max) Voltage - On State (Vtm) (Max) 1.45 V Current - On State (It (AV)) (Max) 800mA Current - On State (It (RMS)) (Max) 1.25 A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) SCR Type Sensitive Gate Operating Temperature 40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Package	TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)	
Voltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.45 VCurrent - On State (It (AV)) (Max)800mACurrent - On State (It (RMS)) (Max)1.25 ACurrent - Hold (Ih) (Max)5mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)22.5 A, 25 ASCR TypeSensitive GateOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Series	-	
Current - Gate Trigger (Igt) (Max) Voltage - On State (Vtm) (Max) 1.45V Current - On State (It (AV)) (Max) 800mA Current - On State (It (RMS)) (Max) 1.25A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) 22.5A, 25A SCR Type Sensitive Gate Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Voltage - Off State	400V	
Voltage - On State (Vtm) (Max) Current - On State (It (AV)) (Max) 800mA Current - On State (It (RMS)) (Max) 1.25A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) 22.5A, 25A SCR Type Sensitive Gate Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Voltage - Gate Trigger (Vgt) (Max)	800mV	
Current - On State (It (AV)) (Max) Current - On State (It (RMS)) (Max) 1.25A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) 5CR Type Sensitive Gate Operating Temperature 40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Current - Gate Trigger (Igt) (Max)	200μΑ	
Current - On State (It (RMS)) (Max) 1.25A Current - Hold (Ih) (Max) 5mA Current - Off State (Max) 5µA Current - Non Rep. Surge 50, 60Hz (Itsm) 22.5A, 25A SCR Type Sensitive Gate Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Voltage - On State (Vtm) (Max)	1.45V	
Current - Hold (Ih) (Max)5mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)22.5A, 25ASCR TypeSensitive GateOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Current - On State (It (AV)) (Max)	800mA	
Current - Off State (Max) $5\mu A$ Current - Non Rep. Surge 50, 60Hz (Itsm) $22.5A, 25A$ SCR Type Sensitive Gate Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Current - On State (It (RMS)) (Max)	1.25A	
Current - Non Rep. Surge 50, 60Hz (Itsm) 22.5A, 25A SCR Type Sensitive Gate -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Current - Hold (Ih) (Max)	5mA	
SCR TypeSensitive GateOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Current - Off State (Max)	5μΑ	
Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Current - Non Rep. Surge 50, 60Hz (Itsm)	22.5A, 25A	
Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	SCR Type	Sensitive Gate	
Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Operating Temperature	-40°C ~ 125°C	
Supplier Device Package TO-92-3	Mounting Type	Through Hole	
	Package / Case	TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)	
\mathbf{p}	Supplier Device Package	TO-92-3	
Report errors?			Report errors?

X0202DA 5BL2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

X0202DA 5BL2 Payment Methods



















X0202DA 5BL2 Shipping Methods













If you have any question about X0202DA 5BL2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com