

XC5A-6482-1A

XC5A-6482-1A Information

Heisener.com Ottal Write Land Terr	 XC5A-6482-1A Omron Electronics Inc-EMC Div Connectors, Interconnects Backplane Connectors - DIN 41612 DIN CONNECTOR 64 POS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



XC5A-6482-1A Specifications

Manufacturer Part NumberXC5A-6482-1AManufacturerOmron Electronics Inc-EMC DivCategoryConnectors, InterconnectsBackplane Connectors - DIN 41612Package-SeriesXC5Connector TypePug, Male PinsNumber of Positions64Number of Positions LoadedNIIPitch0.100° (2.54mm)Number of Rows2StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleFeatures-Contact Finish ThicknessGold		
CategoryConnectors, InterconnectsBackplane Connectors - DIN 41612Package-SeriesXC5Connector TypePug, Male PinsNumber of Positions64Number of Positions LoadedAllNumber of Rows2StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleFeaturesSolderContact FinishGoldContact Finish ThicknessSign (0.40µm)	Manufacturer Part Number	XC5A-6482-1A
AckageBackplane Connectors - DIN 41612Package-SeriesXC5Connector TypePlug, Male PinsNumber of Positions64Number of Positions LoadedAllNumber of Rows0.100" (2.54mm)StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleFeaturesSolderFeatures-Contact Finish ThicknessGoldKonter Finish ThicknessSolder	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesXC5Connector TypePlug, Male PinsNumber of Positions64Number of Positions LoadedNIPitch0.100" (2.54mm)Number of Rows2StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleFerminationSolderFeatures-Contact FinishGoldContact Finish ThicknessIpin (0.40µm)	Category	Connectors, Interconnects
SeriesXC5Connector TypePlug, Male PinsNumber of Positions64Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows2StyleBLevel, Class-Mounting TypeSolderFeatures.Features-Contact FinishGoldContact Finish Thickness16µin (0.40µm)		Backplane Connectors - DIN 41612
Connector TypePlug, Male PinsNumber of Positions64Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows2StyleBLevel, Class-Mounting TypeSolderFeatures-Features-Contact Finish Thickness6ddMane State-State Finish Thickness-State Finish Thickness-State State State-State State State-State State	Package	-
Number of Positions64Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows2StyleBLevel, Class-Nounting TypeThrough Hole, Right AngleTerminationSolderFeatures-Contact Finish ThicknessGoldContact Finish Thickness16µin (0.40µm)	Series	XC5
Number of Positions LoadedAllPitch0.100" (2.54mm)Number of Rows2StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleFeaturesSolderFontact FinishGoldContact FinishIfun (0.40µm)	Connector Type	Plug, Male Pins
Pitch0.100" (2.54mm)Number of Rows2StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleTerminationSolderFeatures-Contact FinishGoldKunder Strike-Kunder Strike- <t< td=""><td>Number of Positions</td><td>64</td></t<>	Number of Positions	64
Number of Rows2StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleTerminationSolderFeatures-Contact FinishGoldContact Finish Thickness16µin (0.40µm)	Number of Positions Loaded	All
StyleBLevel, Class-Mounting TypeThrough Hole, Right AngleTerminationSolderFeatures-Contact FinishGoldContact Finish Thickness16µin (0.40µm)	Pitch	0.100" (2.54mm)
Level, Class-Mounting TypeThrough Hole, Right AngleTerminationSolderFeatures-Contact FinishGoldContact Finish Thickness16µin (0.40µm)	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderFeatures-Contact FinishGoldContact FinishThickness16µin (0.40µm)	Style	В
TerminationSolderFeatures-Contact FinishGoldContact Finish Thickness16µin (0.40µm)	Level, Class	-
Features-Contact Finish ThicknessGoldContact Finish Thickness16µin (0.40µm)	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness16µin (0.40µm)	Termination	Solder
Contact Finish Thickness 16µin (0.40µm)	Features	-
	Contact Finish	Gold
Demonstration 2	Contact Finish Thickness	16μin (0.40μm)
Report errors?		Report errors?

XC5A-6482-1A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

XC5A-6482-1A Payment Methods WIRE transfer PayPal Methods XC5A-6482-1A Shipping Methods



If you have any question about XC5A-6482-1A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com