

XF-10234

XF-10234 Information



Part Number	XF-10234	
Manufacturer	Amgis, LLC	
Category	Transformers Power Transformers	
Description	XFRMR TOROIDAL 15VA CHAS MOUNT	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



XF-10234 Specifications

Manufacturer Part NumberXF-10234ManufacturerAmgis, LLCCategoryTransformersPackage-Series-TypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)DualSecondary Winding(s)DualPower - Max15 VAMounting TypeChassis MountFarmination StyleSize / DimensionSize / Dimension57.50mm DiaHeight - Seated (Max)6000YrmsWeicht6000Yrms		
CategoryTarsformersPackage-Package-Series-TypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 17MA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max15 VAMounting TypeChasis MountTermination StyleSize / DimensionSize / Dimension57.50mm DiaHeight - Seated (Max)34.00Wrms	Manufacturer Part Number	XF-10234
Power TransformersPackage-Series-TypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 14TmA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChasis MountSize / Dimension57.50mm DiaSize / Dimension44.00mmVoltage - Isolation400Vrms	Manufacturer	Amgis, LLC
Package-Series-TypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 14TmA, Series 209mAPrimary Winding(s)OualSecondary Winding(s)NoPower - Max15 VAPower - MaxSis MountPrimation StyleMire LeadsSize / Dimension7.50mm DiaHeight - Seated (Max)34.00mmVoltage - Isolation4000Vrms	Category	Transformers
Series-TypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 417mA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)4000Vrms		Power Transformers
TypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 117mA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleS7.50mm DiaSize / Dimension57.50mm DiaHeight - Seated (Max)4000Vrms	Package	-
Y115V, 230VVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 417mA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleS7.50mm DiaSize / Dimension57.50mm DiaHeight - Seated (Max)4000Vrms	Series	-
Voltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 417mA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Туре	Toroidal
Current - Output (Max)Parallel 417mA, Series 209mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)DualCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Current - Output (Max)	Parallel 417mA, Series 209mA
Center TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Primary Winding(s)	Dual
Power - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Secondary Winding(s)	Dual
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Center Tap	No
Termination StyleWire LeadsSize / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Power - Max	15 VA
Size / Dimension57.50mm DiaHeight - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Mounting Type	Chassis Mount
Height - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Termination Style	Wire Leads
Voltage - Isolation 4000Vrms	Size / Dimension	57.50mm Dia
-	Height - Seated (Max)	24.00mm
Weight 0.578 lb (262, 18g)	Voltage - Isolation	4000Vrms
	Weight	0.578 lb (262.18g)
Report errors		Report errors?

XF-10234 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about XF-10234, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com