

# XG-2121CA 100.0000M-LHPAL3

### XG-2121CA 100.0000M-LHPAL3 Information



For Reference Only

Part Number XG-2121CA 100.0000M-LHPAL3

Manufacturer EPSON

Category Crystals, Oscillators, Resonators

Oscillators

**Description** OSC SO 100.000MHZ LVDS SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## XG-2121CA 100.0000M-LHPAL3 Specifications

Manufacturer Part NumberXG-2121CA 100.0000M-LHPAL3ManufacturerEPSONCategoryCrystals, Oscillators, ResonatorsPackage6-SMD, No LeadSeriesXG-2121CATypeSO (SAW)Frequency100MHzFunctionEnable/DisableOutputLVDSVoltage - Supply2.5VFrequency Stability±100ppmOperating Temperature0°C ~ 70°CCurrent - Supply (Max)30mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height - Seated (Max)0.055" (1.40mm)		
Category         Crystals, Oscillators, Resonators           Package         6-SMD, No Lead           Series         XG-2121CA           Type         SO (SAW)           Frequency         100MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         2.5V           Frequency Stability         ±100ppm           Operating Temperature         0°C ~ 70°C           Current - Supply (Max)         30mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height - Seated (Max)         0.055" (1.40mm)	Manufacturer Part Number	XG-2121CA 100.0000M-LHPAL3
Package         6-SMD, No Lead           Series         XG-2121CA           Type         SO (SAW)           Frequency         100MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         2.5V           Frequency Stability         ±100ppm           Operating Temperature         0°C ~ 70°C           Current - Supply (Max)         30mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height - Seated (Max)         0.055" (1.40mm)	Manufacturer	EPSON
Package         6-SMD, No Lead           Series         XG-2121CA           Type         SO (SAW)           Frequency         100MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         2.5V           Frequency Stability         ±100ppm           Operating Temperature         0°C ~ 70°C           Current - Supply (Max)         30mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height - Seated (Max)         0.055" (1.40mm)	Category	Crystals, Oscillators, Resonators
Series         XG-2121CA           Type         SO (SAW)           Frequency         100MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         2.5V           Frequency Stability         ±100ppm           Operating Temperature         0°C ~ 70°C           Current - Supply (Max)         30mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height - Seated (Max)         0.055" (1.40mm)		Oscillators
Type SO (SAW) Frequency 100MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±100ppm Operating Temperature 0°C ~ 70°C Current - Supply (Max) 30mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.055" (1.40mm)	Package	6-SMD, No Lead
Frequency         100MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         2.5V           Frequency Stability         ±100ppm           Operating Temperature         0°C ~ 70°C           Current - Supply (Max)         30mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height - Seated (Max)         0.055" (1.40mm)	Series	XG-2121CA
Function Enable/Disable Output LVDS  Voltage - Supply 2.5V  Frequency Stability ±100ppm Operating Temperature 0°C ~ 70°C Current - Supply (Max) 30mA  Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.055" (1.40mm)	Туре	SO (SAW)
OutputLVDSVoltage - Supply2.5VFrequency Stability±100ppmOperating Temperature0°C ~ 70°CCurrent - Supply (Max)30mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height - Seated (Max)0.055" (1.40mm)	Frequency	100MHz
Voltage - Supply       2.5V         Frequency Stability       ±100ppm         Operating Temperature       0°C ~ 70°C         Current - Supply (Max)       30mA         Ratings       -         Mounting Type       Surface Mount         Package / Case       6-SMD, No Lead         Size / Dimension       0.276" L x 0.197" W (7.00mm x 5.00mm)         Height - Seated (Max)       0.055" (1.40mm)	Function	Enable/Disable
Frequency Stability ±100ppm  Operating Temperature 0°C ~ 70°C  Current - Supply (Max) 30mA  Ratings -  Mounting Type Surface Mount  Package / Case 6-SMD, No Lead  Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height - Seated (Max) 0.055" (1.40mm)	Output	LVDS
Operating Temperature  O°C ~ 70°C  Current - Supply (Max)  Ratings  -  Mounting Type  Surface Mount  Package / Case  6-SMD, No Lead  Size / Dimension  0.276" L x 0.197" W (7.00mm x 5.00mm)  Height - Seated (Max)  0.055" (1.40mm)	Voltage - Supply	2.5V
Current - Supply (Max)       30mA         Ratings       -         Mounting Type       Surface Mount         Package / Case       6-SMD, No Lead         Size / Dimension       0.276" L x 0.197" W (7.00mm x 5.00mm)         Height - Seated (Max)       0.055" (1.40mm)	Frequency Stability	±100ppm
Ratings -  Mounting Type Surface Mount  Package / Case 6-SMD, No Lead  Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height - Seated (Max) 0.055" (1.40mm)	Operating Temperature	0°C ~ 70°C
Mounting Type Surface Mount  Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height - Seated (Max) 0.055" (1.40mm)	Current - Supply (Max)	30mA
Package / Case       6-SMD, No Lead         Size / Dimension       0.276" L x 0.197" W (7.00mm x 5.00mm)         Height - Seated (Max)       0.055" (1.40mm)	Ratings	-
Size / Dimension       0.276" L x 0.197" W (7.00mm x 5.00mm)         Height - Seated (Max)       0.055" (1.40mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.055" (1.40mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height - Seated (Max)	0.055" (1.40mm)
		Report errors?

### XG-2121CA 100.0000M-LHPAL3 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### XG-2121CA 100.0000M-LHPAL3 Payment Methods



















## XG-2121CA 100.0000M-LHPAL3 Shipping Methods













If you have any question about XG-2121CA 100.0000M-LHPAL3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com