

XLH536020.000000I

XLH536020.000000I Information

	 XLH536020.000000I IDT, Integrated Device Technology Inc Crystals, Oscillators, Resonators Oscillators OSC XO 20.000MHZ HCMOS SMD 4-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



XLH536020.000000I Specifications

ManufacturerIDT, Integrated Device Technology IncCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage4-SMD, No LeadSeriesXPRESSO? FXO-HC53TypeXO (Standard)Frequency20MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability425pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)Surface MountRatings-Mounting TypeSurface MountPackage / CaseSurface MountSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage4-SMD, No LeadSeriesXPRESSO? FXO-HC53TypeXO (Standard)Frequency20MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.023" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Manufacturer Part Number	XLH536020.000000I
OscillatorsPackage4-SMD, No LeadSeriesXPRESSO? FXO-HC53TypeXO (Standard)Frequency20MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.035" (1.40mm)	Manufacturer	IDT, Integrated Device Technology Inc
Package 4-SMD, No Lead Series XPRESSO? FXO-HC53 Type XO (Standard) Frequency 20MHz Function Enable/Disable Output HCMOS Voltage - Supply 3.3V Frequency Stability 4.0°C ~ 85°C Ourput 32mA Ratings - Mounting Type Surface Mount Package / Case 4.SMD, No Lead Size / Dimension 0.203" L x 0.132" W (5.15mm x 3.35mm) Height - Seated (Max) 0.055" (1.40mm)	Category	Crystals, Oscillators, Resonators
SeriesXPRESSO? FXO-HC53TypeXO (Standard)Frequency20MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4.5MD, No LeadSize / Dimension0.055" (1.40mm)		Oscillators
TypeXO (Standard)Frequency20MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.023" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Package	4-SMD, No Lead
Frequency20MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Series	XPRESSO? FXO-HC53
FunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Туре	XO (Standard)
OutputHCMOSVoltage - Supply3.3VFrequency Stability±25pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Frequency	20MHz
Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 32mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.203" L x 0.132" W (5.15mm x 3.35mm) Height - Seated (Max) 0.055" (1.40mm)	Function	Enable/Disable
Frequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Output	HCMOS
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Voltage - Supply	3.3V
Current - Supply (Max)32mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Frequency Stability	±25ppm
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Operating Temperature	-40°C ~ 85°C
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.203" L x 0.132" W (5.15mm x 3.35mm)Height - Seated (Max)0.055" (1.40mm)	Current - Supply (Max)	32mA
Package / Case 4-SMD, No Lead Size / Dimension 0.203" L x 0.132" W (5.15mm x 3.35mm) Height - Seated (Max) 0.055" (1.40mm)	Ratings	-
Size / Dimension 0.203" L x 0.132" W (5.15mm x 3.35mm) Height - Seated (Max) 0.055" (1.40mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.055" (1.40mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.203" L x 0.132" W (5.15mm x 3.35mm)
Report errors?	Height - Seated (Max)	0.055" (1.40mm)
		Report errors?

XLH536020.000000I Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

XLH536020.000000I Payment Methods





If you have any question about XLH536020.000000I, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com