

XLH736075.000000I

XLH736075.000000I Information

www.heisener.com	 XLH736075.000000I IDT, Integrated Device Technology Inc Crystals, Oscillators, Resonators Oscillators OSC XO 75.000MHZ HCMOS SMD 4-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



XLH736075.000000I Specifications

ManufacturerIDT, Integrated Device Technology IncCategoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsPackage4.SMD, No LeadSeriesXPRESSO? FXO-HC73StreguencyXO (Standard)FrequencyFomble/DisableDuputHCMOSVoltage - Supply3.3VSeriens-Ourput, Supply (Max)4.7mACurrent - Supply (Max)-Annual-Package / Case4.SMD, No LeadPackage / Case-Backage / Case-Bight - Seated (Max)0.SDS" (1.40mm)		
CategoryCrystals, Oscillators, ResonatorsOscillatorsPackage4-SMD, No LeadSeriesXPRESSO? FXO-HC73TypeXO (Standard)Frequency75MHzFunctionEnable/DisableDutputHCMOSVoltage - Supply3.3VFrequency Stability±25pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)47mARatings-Package / Case4.SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Manufacturer Part Number	XLH736075.000000I
OscillatorsPackage4-SMD, No LeadPackageXPRESSO? FXO-HC73SteriesXPRESSO? FXO-HC73TypeXO (Standard)Frequency75MHzFunctionEnable/DisableDutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)47mARatings-Package / Case4.SMD, No LeadBize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Manufacturer	IDT, Integrated Device Technology Inc
Package 4-SMD, No Lead Series XPRESSO? FXO-HC73 Type XO (standard) Frequency 75MHz Function Enable/Disable Dutput HCMOS Voltage - Supply 3.3V Prequency Stability ±25ppm Duperating Temperature -40°C ~ 85°C Current - Supply (Max) 47mA Ratings - Package / Case 4.SMD, No Lead Bize / Dimension 0.295" L x 0.205" W (7.50mm x 5.20mm) Height - Seated (Max) 0.055" (1.40mm)	Category	Crystals, Oscillators, Resonators
SeriesXPRESSO? FXO-HC73TypeXO (Standard)Frequency75MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)3.urface MountRatings-Package / Case4.SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.55" (1.40mm)		Oscillators
TypeXO (Standard)Frequency75MHzFunctionEnable/DisableDutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)7mARatings-Package / Case4.5MD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Package	4-SMD, No Lead
Frequency 75MHz Function Enable/Disable Dutput HCMOS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 47mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.295" L x 0.205" W (7.50mm x 5.20mm) Height - Seated (Max) 0.055" (1.40mm)	Series	XPRESSO? FXO-HC73
FunctionEnable/DisableDutputHCMOSVoltage - Supply3.3VFrequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)47mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Туре	XO (Standard)
DutputHCMOSVoltage - Supply3.3VFrequency Stability±25pmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)47mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Frequency	75MHz
Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -40°C ~ 85°C Current - Supply (Max) 47mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.295" L x 0.205" W (7.50mm x 5.20mm)	Function	Enable/Disable
Frequency Stability±25ppmOperating Temperature-40°C ~ 85°CCurrent - Supply (Max)47mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Output	HCMOS
Operating Temperature-40°C ~ 85°CCurrent - Supply (Max)47mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Voltage - Supply	3.3V
Current - Supply (Max)47mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Frequency Stability	±25ppm
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Operating Temperature	-40°C ~ 85°C
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.295" L x 0.205" W (7.50mm x 5.20mm)Height - Seated (Max)0.055" (1.40mm)	Current - Supply (Max)	47mA
Package / Case 4-SMD, No Lead Size / Dimension 0.295" L x 0.205" W (7.50mm x 5.20mm) Height - Seated (Max) 0.055" (1.40mm)	Ratings	-
Size / Dimension 0.295" L x 0.205" W (7.50mm x 5.20mm) Height - Seated (Max) 0.055" (1.40mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.055" (1.40mm)	Package / Case	4-SMD, No Lead
•	Size / Dimension	0.295" L x 0.205" W (7.50mm x 5.20mm)
Report errors?	Height - Seated (Max)	0.055" (1.40mm)
		Report errors?

XLH736075.000000I Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

XLH736075.000000I Payment Methods





If you have any question about XLH736075.000000I, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com