



XLUY34D Information



For Reference Only

Part Number XLUY34D Manufacturer SunLED

Category Optoelectronics

LED Indication - Discrete

Description LED YELLOW DIFF 3MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XLUY34D Specifications

Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95 V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 588nm Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm		Report errors?
Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 588nm Wavelength - Peak 590nm Features - Package / Case Radial Supplier Device Package T-1 (3mm)	Height (Max)	5.00mm
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 588nm Wavelength - Peak 590nm Features - Package / Case Radial	Size / Dimension	-
LED Indication - Discrete Package Radial Series - Color Yellow Configuration Lens Color Yellow Lens Transparency Diffused Millicandela Rating Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant Wavelength - Peak 590nm Features -	Supplier Device Package	T-1 (3mm)
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 588nm Wavelength - Peak 590nm	Package / Case	Radial
LED Indication - Discrete Package Radial Series - Color Yellow Configuration Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 588nm	Features	-
Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole	Wavelength - Peak	590nm
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA Viewing Angle 60°	Wavelength - Dominant	588nm
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 10mA	Mounting Type	Through Hole
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 1.95V	Viewing Angle	60°
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm		10mA
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow Lens Transparency Diffused Millicandela Rating 14mcd	-	-
LED Indication - DiscretePackageRadialSeries-ColorYellowConfiguration-Lens ColorYellowLens TransparencyDiffused	-	Round with Domed Top, 3mm (T-1), 3.00mm
LED Indication - Discrete Package Radial Series - Color Yellow Configuration - Lens Color Yellow		14mcd
LED Indication - Discrete Package Radial Series - Color Yellow Configuration -	Lens Transparency	Diffused
LED Indication - Discrete Package Radial Series - Color Yellow	-	Yellow
LED Indication - Discrete Package Radial Series -	Configuration	-
LED Indication - Discrete Package Radial		Yellow
LED Indication - Discrete	-	
	Package	
Catagory	Category	-
Manufacturer Suilled		
Manufacturer Part Number XLUY34D Manufacturer SunLED		

XLUY34D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XLUY34D Payment Methods





















XLUY34D Shipping Methods













If you have any question about XLUY34D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com