



XLUYR34M Information



For Reference Only

Part Number XLUYR34M Manufacturer SunLED

Category Optoelectronics

LED Indication - Discrete

Description LED RED/YLW DIFF 3MM ROUND T/H

Package Radial - 3 Lead, Formed

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XLUYR34M Specifications

Manufacturer Part Number XLUYR34M Manufacturer SunLED Category Optoelectronics LED Indication - Discrete Package Radial - 3 Lead, Formed Series - Color Red, Yellow Configuration Common Cathode Lens Color White Lens Transparency Diffused Millicandela Rating 15mcd Red, 19mcd Yellow Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	•	
Category Doptoelectronics LED Indication - Discrete Radial - 3 Lead, Formed Series - Color Red, Yellow Configuration Common Cathode Lens Color White Lens Transparency Diffused Millicandela Rating 15mcd Red, 19mcd Yellow Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Vavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Manufacturer Part Number	XLUYR34M
LED Indication - Discrete Package Radial - 3 Lead, Formed Series - Color Red, Yellow Configuration Common Cathode Lens Color White Lens Transparency Diffused Millicandela Rating 15mcd Red, 19mcd Yellow Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Manufacturer	SunLED
Package Radial - 3 Lead, Formed Series - Color Red, Yellow Configuration Common Cathode Lens Color White Lens Transparency Diffused Millicandela Rating 15mcd Red, 19mcd Yellow Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Category	Optoelectronics
Series - Color Red, Yellow Configuration Common Cathode Lens Color White Lens Transparency Diffused Millicandela Rating 15mcd Red, 19mcd Yellow Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm		LED Indication - Discrete
ColorRed, YellowConfigurationCommon CathodeLens ColorWhiteLens TransparencyDiffusedMillicandela Rating15mcd Red, 19mcd YellowLens Style/SizeRound with Domed Top, 3mm (T-1), 3.00mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant617nm Red, 588nm YellowWavelength - Peak627nm Red, 590nm YellowFeatures-Package / CaseRadial - 3 Lead, FormedSupplier Device PackageT-1 (3mm)Size / Dimension-Height (Max)5.00mm	Package	Radial - 3 Lead, Formed
Configuration Lens Color White Lens Transparency Diffused Millicandela Rating Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) Signaria Ageles White White Bright (Max) Signaria Ageles Bright (Series	-
Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating15mcd Red, 19mcd YellowLens Style/SizeRound with Domed Top, 3mm (T-1), 3.00mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant617nm Red, 588nm YellowWavelength - Peak627nm Red, 590nm YellowFeatures-Package / CaseRadial - 3 Lead, FormedSupplier Device PackageT-1 (3mm)Size / Dimension-Height (Max)5.00mm	Color	Red, Yellow
Lens Transparency Millicandela Rating 15mcd Red, 19mcd Yellow Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Configuration	Common Cathode
Millicandela Rating Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension Lens Style/Size Round Yellow Teatures - Radial - 3 Lead, Formed T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Lens Color	White
Lens Style/Size Round with Domed Top, 3mm (T-1), 3.00mm Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Millicandela Rating	15mcd Red, 19mcd Yellow
Current - Test 20mA Red, 20mA Yellow Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Lens Style/Size	Round with Domed Top, 3mm (T-1), 3.00mm
Viewing Angle60°Mounting TypeThrough HoleWavelength - Dominant617nm Red, 588nm YellowWavelength - Peak627nm Red, 590nm YellowFeatures-Package / CaseRadial - 3 Lead, FormedSupplier Device PackageT-1 (3mm)Size / Dimension-Height (Max)5.00mm	Voltage - Forward (Vf) (Typ)	2V Red, 2.1V Yellow
Mounting Type Through Hole Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Current - Test	20mA Red, 20mA Yellow
Wavelength - Dominant 617nm Red, 588nm Yellow Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Viewing Angle	60°
Wavelength - Peak 627nm Red, 590nm Yellow Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Mounting Type	Through Hole
Features - Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Wavelength - Dominant	617nm Red, 588nm Yellow
Package / Case Radial - 3 Lead, Formed Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Wavelength - Peak	627nm Red, 590nm Yellow
Supplier Device Package T-1 (3mm) Size / Dimension - Height (Max) 5.00mm	Features	-
Size / Dimension - Height (Max) 5.00mm	Package / Case	Radial - 3 Lead, Formed
Height (Max) 5.00mm	Supplier Device Package	T-1 (3mm)
	Size / Dimension	-
Report errors?	Height (Max)	5.00mm
		Report errors?

XLUYR34M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XLUYR34M Payment Methods



















XLUYR34M Shipping Methods













If you have any question about XLUYR34M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com