

XM2F-0910-132 Information

Heisener.com

Part Number XM2F-0910-132

Manufacturer Omron Electronics Inc-EMC Div

Category Connectors, Interconnects

D-Sub Connectors

Description CONN D-SUB RCPT 9POS VERT SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XM2F-0910-132 Specifications

Manufacturer Part Number XM2F-0910-132 Manufacturer Omron Electronics Inc-EMC Div Category Connectors, Interconnects D-Sub Connectors Package - Series XM2 Connector Style D-Sub Connector Type Receptacle, Female Sockets Number of Positions 9 Number of Rows 2 Shell Size, Connector Layout 1 (DE, E) Contact Type Signal Mounting Type Through Hole Flange Feature - Termination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish - Contact Finish Thickness Flash Ingress Protection - Material Flammability Rating UL94 V-0	•	
CategoryConnectors, InterconnectsPackage-SeriesXM2Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange Feature-TerminationSolderFeaturesShieldedShell Material, FinishSteel, Nickel PlatedContact Finish-Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	XM2F-0910-132
Package - Series XM2 Connector Style D-Sub Connector Type Receptacle, Female Sockets Number of Positions 9 Number of Rows 2 Shell Size, Connector Layout 1 (DE, E) Contact Type Signal Mounting Type Through Hole Flange Feature - Femination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish Thickness Flash Ingress Protection - Material Flammability Rating UL94 V-0	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesXM2Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange Feature-TerminationSolderFeaturesShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesXM2Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange Feature-TerminationSolderFeaturesShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange Feature-TerminationSolderFeaturesShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector Type Receptacle, Female Sockets Number of Positions 9 Number of Rows 2 Shell Size, Connector Layout 1 (DE, E) Contact Type Signal Mounting Type Through Hole Flange Feature - Termination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish Thickness Ingress Protection Material Flammability Rating UL94 V-0	Series	XM2
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange Feature-TerminationSolderFeaturesShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange Feature-TerminationSolderFeaturesShieldedShell Material, FinishSteel, Nickel PlatedContact Finish-Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout Contact Type Signal Mounting Type Through Hole Flange Feature - Termination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish Thickness Ingress Protection Material Flammability Rating 1 (DE, E) Signal 2 (DE,	Number of Positions	9
Contact Type Signal Mounting Type Through Hole Flange Feature - Termination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish Thickness Flash Ingress Protection - Material Flammability Rating UL94 V-0	Number of Rows	2
Mounting Type Through Hole Flange Feature - Termination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish Contact Finish Thickness Ingress Protection Material Flammability Rating UL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange Feature Termination Solder Features Shielded Shell Material, Finish Contact Finish Contact Finish Thickness Ingress Protection Material Flammability Rating	Contact Type	Signal
Termination Solder Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish - Contact Finish Thickness Flash Ingress Protection - Material Flammability Rating UL94 V-0	Mounting Type	Through Hole
Features Shielded Shell Material, Finish Steel, Nickel Plated Contact Finish - Contact Finish Thickness Flash Ingress Protection - Material Flammability Rating UL94 V-0	Flange Feature	-
Shell Material, Finish Contact Finish Contact Finish Thickness Flash Ingress Protection Material Flammability Rating UL94 V-0	Termination	Solder
Contact Finish Contact Finish Thickness Flash Ingress Protection Material Flammability Rating UL94 V-0	Features	Shielded
Contact Finish Thickness Flash Ingress Protection - Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Nickel Plated
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	-
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
Report cross:		Report errors?

XM2F-0910-132 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XM2F-0910-132 Payment Methods



















XM2F-0910-132 Shipping Methods













If you have any question about XM2F-0910-132, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com