

XMC1100T016F0016AAXUMA1

XMC1100T016F0016AAXUMA1 Information



Part Number XMC1100T016F0016AAXUMA1

Manufacturer Infineon Technologies

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 32BIT 16KB FLASH 16TSSOP **Package** 16-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XMC1100T016F0016AAXUMA1 Specifications

Manufacturer Part Number Manufacturer Infineon Technologies Integrated Circuits (ICs) Embedded - Microcontrollers Package 16-TSSOP (0.173", 4.40mm Width) Series XMC1000 Core Processor ARM? Cortex?-M0 Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size Program Memory Type EEPROM Size RAM Size Voltage - Supply (Vcc/Vdd) Infineon Technologies Infin
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 16-TSSOP (0.173", 4.40mm Width) Series XMC1000 Core Processor ARM? Cortex?-M0 Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size Integrated Circuits (ICs) Embedded - Microcontrollers 16Cs (1.40mm Width) XMC1000 ARM? Cortex?-M0 22-Bit 32-Bit 32-Bit 32-Bit 32-Bit 32-Bit 32-Bit 32-Bit 32-Bit 32-Bit 43-Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16K x 8)
Embedded - Microcontrollers Package 16-TSSOP (0.173", 4.40mm Width) Series XMC1000 Core Processor ARM? Cortex?-M0 Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Package 16-TSSOP (0.173", 4.40mm Width) Series XMC1000 Core Processor ARM? Cortex?-M0 Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Series XMC1000 Core Processor ARM? Cortex?-M0 Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Core Processor Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Core Size 32-Bit Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Speed 32MHz Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Connectivity I2C, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Peripherals Brown-out Detect/Reset, I2S, POR, PWM, WDT Number of I/O 11 Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Number of I/O Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Program Memory Size 16KB (16K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
Program Memory Type FLASH EEPROM Size - RAM Size 16K x 8
EEPROM Size - RAM Size 16K x 8
RAM Size 16K x 8
Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 5.5 \text{ V}$
Data Converters A/D 6x12b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 16-TSSOP (0.173", 4.40mm Width)
Supplier Device Package PG-TSSOP-16-8
Report error

XMC1100T016F0016AAXUMA1 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XMC1100T016F0016AAXUMA1 Payment Methods





















XMC1100T016F0016AAXUMA1 Shipping Methods













If you have any question about XMC1100T016F0016AAXUMA1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com