



XPCL04GTC Information

Heisener.com

Part Number XPCL04GTC

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS GAUGE 4" H2O 4SIP

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XPCL04GTC Specifications

Manufacturer XPCL04GTC Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 4-SIP Module Series XPCL Pressure Type Vented Gauge Operating Pressure 0.15 PSI (1 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	-	
CategorySensors, TransducersPackage4-SIP ModuleSeriesXPCLPressure TypeVented GaugeOperating Pressure0.15 PSI (1 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (12V)Accuracy±1%Voltage - Supply3 V ~ 16 VPort SizeMale - 0.19" (4.83mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination Style-Maximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	XPCL04GTC
Package 4-SIP Module Series XPCL Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature - 25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 4-SIP Module Series XPCL Pressure Type Vented Gauge Operating Pressure 0.15 PSI (1 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Category	Sensors, Transducers
Series XPCL Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 0.15 PSI (1 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 25 mV (12V) Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 25 mV (12V) Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case Supplier Device Package - Supplier Device Package	Series	XPCL
Output TypeWheatstone BridgeOutput0 mV ~ 25 mV (12V)Accuracy±1%Voltage - Supply3 V ~ 16 VPort SizeMale - 0.19" (4.83mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination Style-Maximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 25 \text{ mV} (12 \text{V})$ Accuracy $\pm 1\%$ Voltage - Supply $3 \text{ V} \sim 16 \text{ V}$ Port Size $Male - 0.19'' (4.83 \text{mm}) \text{ Tube}$ Port Style $Barbed$ Features $Temperature Compensated$ Termination Style $-$ Maximum Pressure $3 \text{ PSI} (20.68 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package $-$	Operating Pressure	0.15 PSI (1 kPa)
Accuracy ±1% Voltage - Supply 3 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply3 V ~ 16 VPort SizeMale - 0.19" (4.83mm) TubePort StyleBarbedFeaturesTemperature CompensatedTermination Style-Maximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Output	0 mV ~ 25 mV (12V)
Port Size Male - 0.19" (4.83mm) Tube Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±1%
Port Style Barbed Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Voltage - Supply	3 V ~ 16 V
Features Temperature Compensated Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Size	Male - 0.19" (4.83mm) Tube
Termination Style - Maximum Pressure 3 PSI (20.68 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Style	Barbed
Maximum Pressure3 PSI (20.68 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	-
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	3 PSI (20.68 kPa)
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
Report chors.		Report errors?

XPCL04GTC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XPCL04GTC Payment Methods



















XPCL04GTC Shipping Methods













If you have any question about XPCL04GTC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com