

XS2C-A423

a Quote

XS2C-A423 Information

Heisener.com	Part Number	XS2C-A423	
	Manufacturer	Omron Electronics Inc-EMC Div	
	Category	Connectors, Interconnects Circular Connectors	정
	Description	CONN SOCKET 4MM AC STRT SDR	- 19-
	Package	-	- 23
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



XS2C-A423 Specifications

Manufacturer Part NumberXS2C-A423ManufacturerOmron Electronics Inc-EMC DivCategoryConnectorsPackage-SeriesXS2Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Mouning TypeFree Hanging (In-Line)Farening TypeSolderForeitationKeyedNore of PositionsSolderShell Size, MIL-Greing TypeFree Hanging (In-Line)ForeitationSolderForeitationKeyedShell Material, FinishGolgContact FinishGolgFatures-Voltage - RatedStoXCA 125 VDCCurrent RatingStoXCA 125 VDCCurrent RatingAKeport errors?		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesXS2Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderGrientationKeyedIngers ProtectionHord Staff, WaterproofShell Material, FinishGoldContact Finish-Staff Seatures-Yoltage RatedStoXCA, 12SVDCCurrent Rating4A	Manufacturer Part Number	XS2C-A423
AckageCircular ConnectorsPackage-SeriesXS2Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeyedShell Material, FinishCopper Alloy, Nickel PlatedShell Material, FinishGoldFeatures-Voltage - Rated2SOVAC, 12SVDCCurrent Rating4A	Manufacturer	Omron Electronics Inc-EMC Div
Package.SeriesXS2Connector TypeReceptacle Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeydShell Material, FinishCoper Alloy, Nickel PlatedShell Material, FinishGoldFeatures-Fotage RatedSOVAC, 12SVDCKurent Rating64	Category	Connectors, Interconnects
SeriesXS2Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Package	-
Number of Positions4Number of PositionsM12-4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionP67 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Series	XS2
Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCGurrent Rating4A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedFoaturesGoldFoatures-Voltage - Rated250VAC, 125VDCGurrent Rating4A	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeThreadedForentationKeyedOrientationP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCGurent Rating4A	Shell Size - Insert	M12-4
TerminationSolderFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Shell Size, MIL	-
Fastening TypeThreadedFastening TypeKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Termination	Solder
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Fastening Type	Threaded
Shell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Orientation	Keyed
Contact FinishGoldFeatures-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features-Voltage - Rated250VAC, 125VDCCurrent Rating4A	Shell Material, Finish	Copper Alloy, Nickel Plated
Voltage - Rated250VAC, 125VDCCurrent Rating4A	Contact Finish	Gold
Current Rating 4A	Features	-
-	Voltage - Rated	250VAC, 125VDC
Report errors?	Current Rating	4A
		Report errors?

XS2C-A423 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about XS2C-A423, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com