

XS2G-D4S1 Information



For Reference Only

Part Number XS2G-D4S1

Manufacturer Omron Automation and Safety
Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 4POS SCREW FOR SRT2

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XS2G-D4S1 Specifications

Manufacturer Part NumberXS2G-D4S1ManufacturerOmron Automation and SafetyCategoryConnectors, InterconnectsPackage-SeriesXS2Connector TypePlug, Male PinsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesCable ClampVoltage - Rated250VAC, 125VDCCurrent Rating4A		
Category Connectors, Interconnects Circular Connectors Package - Series XS2 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated Current Rating Cable Clamp Value Connectors, Interconnects Circular Connectors AS2 Connectors AS2 AS2 AS2 AS2 AS2 AS2 AS2 AS	Manufacturer Part Number	XS2G-D4S1
Circular Connectors Package - Series XS2 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Contact Finish Gold Features Cable Clamp Voltage - Rated Current Rating Connector S XS2 Connector Type Plug, Male Pins At 4 Connector Mile Pins Copper Alloy, Nickel Plated Contact Finish Gold Cable Clamp Voltage - Rated Corrent Rating 4A	Manufacturer	Omron Automation and Safety
Package-SeriesXS2Connector TypePlug, Male PinsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishCopper Alloy, Nickel PlatedContact FinishGoldFeaturesCable ClampVoltage - Rated250VAC, 125VDCCurrent Rating4A	Category	Connectors, Interconnects
Series XS2 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 44A		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Package	-
Number of Positions Shell Size - Insert M12-4 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Features Cable Clamp Voltage - Rated Current Rating 4A	Series	XS2
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection Ingress Protection Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated Current Rating 4A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Number of Positions	4
Mounting Type Free Hanging (In-Line) Screw Fastening Type Threaded Orientation Keyed Ingress Protection Ingress Protection Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated Current Rating Free Hanging (In-Line) Screw Threaded Copwa Threaded Copwa Threaded Copyer Current Rating Freatures Free Hanging (In-Line) Screw Threaded Copwa Threaded Copyer Cupyer Threaded Copyer Copyer Threaded Copyer Thread	Shell Size - Insert	M12-4
Termination Screw Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating Akeyed Threaded Copper Alloy, Waterproof Copper Alloy, Nickel Plated Akeyed Akeyed Copper Alloy, Nickel Plated Akeyed	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Termination	Screw
Ingress Protection Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated Current Rating IP67 - Dust Tight, Waterproof Copper Alloy, Nickel Plated Copper Alloy, Nickel Plated 4A	Fastening Type	Threaded
Shell Material, Finish Copper Alloy, Nickel Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Orientation	Keyed
Contact Finish Gold Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Cable Clamp Voltage - Rated 250VAC, 125VDC Current Rating 4A	Shell Material, Finish	Copper Alloy, Nickel Plated
Voltage - Rated 250VAC, 125VDC Current Rating 4A	Contact Finish	Gold
Current Rating 4A	Features	Cable Clamp
-	Voltage - Rated	250VAC, 125VDC
Report errors?	Current Rating	4A
		Report errors?

XS2G-D4S1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XS2G-D4S1 Payment Methods



















XS2G-D4S1 Shipping Methods













If you have any question about XS2G-D4S1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com