

XS500-48N-000 Information



For Reference Only

Part Number XS500-48N-000

Manufacturer Excelsys Technologies Ltd

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 500W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XS500-48N-000 Specifications

Manufacturer XS500-48N-000 Manufacturer Excelsys Technologies Ltd Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Xsolo Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.5A Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Xsolo Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.5A Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Manufacturer Part Number	XS500-48N-000
Package - Series Xsolo Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.5A Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Manufacturer	Excelsys Technologies Ltd
Package-SeriesXsoloTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10.5APower (Watts)500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency-Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Xsolo Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.5A Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)		AC DC Converters
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10.5APower (Watts)500WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency-Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Package	-
Number of Outputs1Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 1 $48V$ Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max) $10.5A$ Power (Watts) $500W$ ApplicationsITE (Commercial), MedicalVoltage - Isolation $4kV$ ($4000V$)Efficiency-Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension 9.33° L x 5.04° W x 1.54° H ($237.0\text{mm} \times 128.0\text{mm} \times 39.1\text{mm}$)	Series	Xsolo
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Туре	Open Frame
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.5A Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) 10.5A Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Voltage - Output 3	-
Power (Watts) 500W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Voltage - Output 4	-
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Current - Output (Max)	10.5A
Voltage - Isolation 4kV (4000V) Efficiency - Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Power (Watts)	500W
Efficiency Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Applications	ITE (Commercial), Medical
Operating Temperature -40°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Operating Temperature	-40°C ~ 70 °C (With Derating)
Size / Dimension 9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)	Features	Adjustable Output, DC Input Capable, Remote On/Off, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	9.33" L x 5.04" W x 1.54" H (237.0mm x 128.0mm x 39.1mm)
		Report errors?

XS500-48N-000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XS500-48N-000 Payment Methods



















XS500-48N-000 Shipping Methods













If you have any question about XS500-48N-000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com