



XSM2MOK983W Information



For Reference Only

Part Number XSM2MOK983W

Manufacturer SunLED

Category Optoelectronics

LED Lighting - Color

Description LAMP 7.6MM SQ SUP FLUX OR WTR CL

Package 4-DIP (0.200", 5.08mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XSM2MOK983W Specifications

Manufacturer Part Number XSM2MOK983W Manufacturer SunLED Category Optoelectronics LED Lighting - Color Package 4-DIP (0.200", 5.08mm) Series - Color Orange Wavelength 605nm (Typ) Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)		
Category Optoelectronics LED Lighting - Color Package 4-DIP (0.200", 5.08mm) Series - Color Orange Wavelength 605nm (Typ) Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Manufacturer Part Number	XSM2MOK983W
Package 4-DIP (0.200", 5.08mm) Series - Color Orange Wavelength 605nm (Typ) Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Manufacturer	SunLED
Package 4-DIP (0.200", 5.08mm) Series - Color Orange Wavelength 605nm (Typ) Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Category	Optoelectronics
Series - Color Orange Wavelength 605nm (Typ) Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)		LED Lighting - Color
ColorOrangeWavelength605nm (Typ)Current - Test70mAVoltage - Forward (Vf) (Typ)2VLumens/Watt @ Current - Test64 lm/WCurrent - Max70mAFlux @ Current/Temperature - Test9 lm (Typ)Temperature - Test25°CViewing Angle70°Mounting TypeThrough HolePackage / Case4-DIP (0.200", 5.08mm)Supplier Device Package-Size / Dimension0.300" L x 0.300" W (7.62mm x 7.62mm)Height - Seated (Max)0.183" (4.65mm)	Package	4-DIP (0.200", 5.08mm)
Wavelength 605nm (Typ) Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Series	-
Current - Test 70mA Voltage - Forward (Vf) (Typ) 2V Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Color	Orange
Voltage - Forward (Vf) (Typ) Lumens/Watt @ Current - Test 64 lm/W Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Wavelength	605nm (Typ)
Lumens/Watt @ Current - Test64 lm/WCurrent - Max70mAFlux @ Current/Temperature - Test9 lm (Typ)Temperature - Test25°CViewing Angle70°Mounting TypeThrough HolePackage / Case4-DIP (0.200", 5.08mm)Supplier Device Package-Size / Dimension0.300" L x 0.300" W (7.62mm x 7.62mm)Height - Seated (Max)0.183" (4.65mm)	Current - Test	70mA
Current - Max 70mA Flux @ Current/Temperature - Test 9 lm (Typ) Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Voltage - Forward (Vf) (Typ)	2V
Flux @ Current/Temperature - Test Plux @ Current/Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Lumens/Watt @ Current - Test	64 lm/W
Temperature - Test 25°C Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Current - Max	70mA
Viewing Angle 70° Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Flux @ Current/Temperature - Test	9 lm (Typ)
Mounting Type Through Hole Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Temperature - Test	25°C
Package / Case 4-DIP (0.200", 5.08mm) Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Viewing Angle	70°
Supplier Device Package - Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Mounting Type	Through Hole
Size / Dimension 0.300" L x 0.300" W (7.62mm x 7.62mm) Height - Seated (Max) 0.183" (4.65mm)	Package / Case	4-DIP (0.200", 5.08mm)
Height - Seated (Max) 0.183" (4.65mm)	Supplier Device Package	-
	Size / Dimension	0.300" L x 0.300" W (7.62mm x 7.62mm)
Report errors?	Height - Seated (Max)	0.183" (4.65mm)
		Report errors?

XSM2MOK983W Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XSM2MOK983W Payment Methods



















XSM2MOK983W Shipping Methods













If you have any question about XSM2MOK983W, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com