

XT40.722 Information



For Reference Only

Part Number XT40.722 **Manufacturer** PULS, LP

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description DIN RAIL PSU 960W 72V 13.3A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XT40.722 Specifications

Manufacturer Part Number XT40.722 Manufacturer PULS, LP Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series DIMENSION X Type Enclosed Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 618" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series DIMENSION X Type Enclosed Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Manufacturer Part Number	XT40.722
Package - Series DIMENSION X Type Enclosed Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Manufacturer	PULS, LP
Package - Series DIMENSION X Type Enclosed Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series DIMENSION X Type Enclosed Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Package	-
Number of Outputs 1 Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Series	DIMENSION X
Voltage - Input 360 ~ 552 VAC (3PH) Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Туре	Enclosed
Voltage - Output 1 72V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Number of Outputs	1
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Voltage - Input	360 ~ 552 VAC (3PH)
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 13A Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Voltage - Output 1	72V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension -25°C ~ 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 13A 13A 13A 13A 14B 14B 14B 15A 15B 15B 15B 15B 15B 15B 15	Voltage - Output 3	-
Power (Watts) 960W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation $3kV (3000V)$ Efficiency 95.5% Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension $6.18^{\circ}\text{L} \times 3.78^{\circ}\text{W} \times 4.88^{\circ}\text{H} (157.0 \text{mm} \times 96.0 \text{mm} \times 124.0 \text{mm})$	Current - Output (Max)	13A
Voltage - Isolation $3kV (3000V)$ Efficiency 95.5% Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension $6.18^{\circ}\text{L} \times 3.78^{\circ}\text{W} \times 4.88^{\circ}\text{H} (157.0\text{mm} \times 96.0\text{mm} \times 124.0\text{mm})$	Power (Watts)	960W
Efficiency 95.5% Operating Temperature -25°C ~ 70°C (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension 6.18 " L x 3.78 " W x 4.88 " H (157.0mm x 96.0 mm x 124.0 mm)	Applications	ITE (Commercial)
Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) Features IP20 Mounting Type DIN Rail Size / Dimension $6.18^{\circ}\text{L} \times 3.78^{\circ}\text{W} \times 4.88^{\circ}\text{H}$ (157.0mm x 96.0mm x 124.0mm)	Voltage - Isolation	3kV (3000V)
Features IP20 Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Efficiency	95.5%
Mounting Type DIN Rail Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Size / Dimension 6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)	Features	IP20
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	6.18" L x 3.78" W x 4.88" H (157.0mm x 96.0mm x 124.0mm)
		Report errors?

XT40.722 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XT40.722 Payment Methods

































If you have any question about XT40.722, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com