



XZDGK55W-3 Information

www.heisener.com

For Reference Only

Part Number XZDGK55W-3

Manufacturer SunLED

Category Optoelectronics

LED Indication - Discrete

Description LED GREEN CLEAR 1206 SMD

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XZDGK55W-3 Specifications

Manufacturer Part Number XZDGK55W-3 Manufacturer SunLED Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	*	
Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Manufacturer Part Number	XZDGK55W-3
Package 1206 (3216 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Manufacturer	SunLED
Package 1206 (3216 Metric) Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Category	Optoelectronics
Series - Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm		LED Indication - Discrete
Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Package	1206 (3216 Metric)
Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 2090mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating2090mcdLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)3.3VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant525nmWavelength - Peak515nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm WHeight (Max)1.80mm	Color	Green
Lens TransparencyClearMillicandela Rating2090mcdLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)3.3VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant525nmWavelength - Peak515nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm WHeight (Max)1.80mm	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 3.3V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 525nm Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)3.3VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant525nmWavelength - Peak515nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm WHeight (Max)1.80mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)3.3VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant525nmWavelength - Peak515nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm WHeight (Max)1.80mm	Millicandela Rating	2090mcd
Current - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant525nmWavelength - Peak515nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm WHeight (Max)1.80mm	Lens Style/Size	Round with Domed Top, 1.60mm
Viewing Angle35°Mounting TypeSurface MountWavelength - Dominant525nmWavelength - Peak515nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm WHeight (Max)1.80mm	Voltage - Forward (Vf) (Typ)	3.3V
Mounting Type Surface Mount Wavelength - Dominant S25nm Wavelength - Peak S15nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Current - Test	20mA
Wavelength - Dominant S25nm Wavelength - Peak Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Viewing Angle	35°
Wavelength - Peak 515nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Mounting Type	Surface Mount
Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Wavelength - Dominant	525nm
Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Wavelength - Peak	515nm
Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Features	-
Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.80mm	Package / Case	1206 (3216 Metric)
Height (Max) 1.80mm	Supplier Device Package	2-SMD
	Size / Dimension	3.20mm L x 1.60mm W
	Height (Max)	1.80mm
Report errors?		Report errors?

XZDGK55W-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XZDGK55W-3 Payment Methods





















XZDGK55W-3 Shipping Methods













If you have any question about XZDGK55W-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com