

XZMDKCBDDG45S-9

XZMDKCBDDG45S-9 Information



For Reference Only

Part Number	XZMDKCBDDG45S-9
Manufacturer	SunLED
Category	Optoelectronics LED Indication - Discrete
Description	LED RGB CLEAR 4SMD GW
Package	4-SMD, Gull Wing
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



XZMDKCBDDG45S-9 Specifications

Manufacturer SunLED Category Optoelectronics LED Indication - Discrete Package 4-SMD, Gull Wing Series - Color Red, Green, Blue (RGB) Configuration Common Anode Configuration Colorless Lens Stole Rating OBmed Red, 497mcd Green, 98mcd Blue Villicandela Rating 108mcd Red, 497mcd Green, 98mcd Blue Voltage - Forward (Vf) (Typ) 1.95V Red, 3.3V Green, 3.3V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 100m Red, 525nm Green, 465nm Blue Wavelength - Peak 630nm Red, 515nm Green, 460nm Blue Features - Package / Case 4-SMD, Gull Wing Supplier Device Package 4-SMD, Gull Wing Supplier Device Package 3.20mm L x 2.80mm W	_	
CategoryOptoelectronicsLED Indication - DiscretePackage4-SMD, Gull WingSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeConson ColoressColorlessColaresNom with Flat Top, 2.40mmVillacadela Rating108mcd Red, 497mcd Green, 98mcd BlueVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle100°Wavelength - Dominant630nm Red, 525nm Green, 465nm BlueVavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Manufacturer Part Number	XZMDKCBDDG45S-9
LED Indication - DiscretePackage4-SMD, Gull WingSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessColor and Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueVavelength - Peak-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W	Manufacturer	SunLED
Package4-SMD, Gull WingSeries-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeLens ColorColorlessLens ColorClearWillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViveing Angle100°Wavelength - Dominant630nm Red, 525nm Green, 465nm BlueVavelength - Peak645nm Red, 515nm Green, 460nm BlueVavelength - Peak4-SMD, Gull WingSepplier Device Package4-PLCCSize / Dimension3.20mm Lx 2.80mm WHeight (Max)1.90mm	Category	Optoelectronics
Series-ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeCeners ColorColorlessCeners TransparencyClearWillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Wouting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BluePackage / Case-Surplier Device Package4-SMD, Gull WingSupplier Device Package3.20mm L x 2.80mm WHeight (Max)1.90mm		LED Indication - Discrete
ColorRed, Green, Blue (RGB)ConfigurationCommon AnodeConsmon AnodeColorlessCener StransparencyClearWillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Woutning TypeSurface Mount, Bottom EntryWavelength - Peak645nm Red, 515nm Green, 465nm BlueFeatures-Package / Case4-SMD, Guill WingSupplier Device Package3.20mm L x 2.80mm WHeight (Max)1.90mm	Package	4-SMD, Gull Wing
ConfigurationCommon AnodeLens ColorColorlessLens TransparencyClearWillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueFeatures-Package / Case4.SMD, Gull WingSupplier Device Package4.PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Color	Red, Green, Blue (RGB)
Lens TransparencyClearMillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueBeatures-Package / Case4-SMD, Gull WingSupplier Device Package320mm L x 2.80mm WBize / Dimension1.90mm	Configuration	Common Anode
Millicandela Rating108mcd Red, 497mcd Green, 98mcd BlueMillicandela Rating108mcd Red, 497mcd Green, 98mcd BlueLens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Lens Color	Colorless
Lens Style/SizeRound with Flat Top, 2.40mmVoltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package3.20mm L x 2.80mm WHeight (Max)1.90mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)1.95V Red, 3.3V Green, 3.3V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package3.20mm L x 2.80mm WHeight (Max)1.90mm	Millicandela Rating	108mcd Red, 497mcd Green, 98mcd Blue
Current - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Lens Style/Size	Round with Flat Top, 2.40mm
Viewing Angle120°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Voltage - Forward (Vf) (Typ)	1.95V Red, 3.3V Green, 3.3V Blue
Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Current - Test	20mA Red, 20mA Green, 20mA Blue
Wavelength - Dominant630nm Red, 525nm Green, 465nm BlueWavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Viewing Angle	120°
Wavelength - Peak645nm Red, 515nm Green, 460nm BlueFeatures-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Mounting Type	Surface Mount, Bottom Entry
Features-Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Wavelength - Dominant	630nm Red, 525nm Green, 465nm Blue
Package / Case4-SMD, Gull WingSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Wavelength - Peak	645nm Red, 515nm Green, 460nm Blue
Supplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm WHeight (Max)1.90mm	Features	-
Size / Dimension 3.20mm L x 2.80mm W Height (Max) 1.90mm	Package / Case	4-SMD, Gull Wing
Height (Max) 1.90mm	Supplier Device Package	4-PLCC
	Size / Dimension	3.20mm L x 2.80mm W
Report errors'	Height (Max)	1.90mm
		Report errors

XZMDKCBDDG45S-9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

XZMDKCBDDG45S-9 Payment Methods



If you have any question about XZMDKCBDDG45S-9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com