



XZMDKVG55W-7 Information



For Reference Only

Part Number XZMDKVG55W-7

Manufacturer SunLED

Category Optoelectronics

LED Indication - Discrete

Description LED GREEN/RED CLEAR 1206 SMD

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









XZMDKVG55W-7 Specifications

Manufacturer Part Number XZMDKVG55W-7 Manufacturer SunLED Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green, Red Configuration Bidirectional Lens Color Colorless Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	•	
Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green, Red Configuration Bidirectional Lens Color Colorless Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Manufacturer Part Number	XZMDKVG55W-7
Package 1206 (3216 Metric) Series - Color Green, Red Configuration Bidirectional Lens Color Colorless Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Manufacturer	SunLED
Package 1206 (3216 Metric) Series - Color Green, Red Configuration Bidirectional Lens Color Colorless Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Category	Optoelectronics
Series - Color Green, Red Configuration Bidirectional Lens Color Colorless Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W		LED Indication - Discrete
ColorGreen, RedConfigurationBidirectionalLens ColorColorlessLens TransparencyClearMillicandela Rating248mcd Green, 397mcd RedLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)2.1V Green, 1.95V RedCurrent - Test20mA Green, 20mA RedViewing Angle40°Mounting TypeSurface MountWavelength - Dominant570nm Green, 630nm RedWavelength - Peak574nm Green, 645nm RedFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Package	1206 (3216 Metric)
Configuration Lens Color Colorless Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension Size / Dimension Size / Dimension Clear Colorless Colorless Red 40° Round with Domed Top, 1.60mm Size / Green, 397mcd Red	Series	-
Lens Color Lens Transparency Clear Millicandela Rating 248mcd Green, 397mcd Red Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W	Color	Green, Red
Lens TransparencyClearMillicandela Rating248mcd Green, 397mcd RedLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)2.1V Green, 1.95V RedCurrent - Test20mA Green, 20mA RedViewing Angle40°Mounting TypeSurface MountWavelength - Dominant570nm Green, 630nm RedWavelength - Peak574nm Green, 645nm RedFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Configuration	Bidirectional
Millicandela Rating Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1 V Green, 1.95 V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W	Lens Color	Colorless
Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) 2.1V Green, 1.95V Red Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Millicandela Rating	248mcd Green, 397mcd Red
Current - Test 20mA Green, 20mA Red Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Lens Style/Size	Round with Domed Top, 1.60mm
Viewing Angle40°Mounting TypeSurface MountWavelength - Dominant570nm Green, 630nm RedWavelength - Peak574nm Green, 645nm RedFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Voltage - Forward (Vf) (Typ)	2.1V Green, 1.95V Red
Mounting Type Surface Mount Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Current - Test	20mA Green, 20mA Red
Wavelength - Dominant 570nm Green, 630nm Red Wavelength - Peak 574nm Green, 645nm Red	Viewing Angle	40°
Wavelength - Peak 574nm Green, 645nm Red Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Mounting Type	Surface Mount
Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Wavelength - Dominant	570nm Green, 630nm Red
Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Wavelength - Peak	574nm Green, 645nm Red
Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Features	-
Size / Dimension 3.20mm L x 1.60mm W	Package / Case	1206 (3216 Metric)
	Supplier Device Package	2-SMD
	Size / Dimension	3.20mm L x 1.60mm W
Height (Max) 1.80mm	Height (Max)	1.80mm
Report errors?		Report errors?

XZMDKVG55W-7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

XZMDKVG55W-7 Payment Methods



















XZMDKVG55W-7 Shipping Methods













If you have any question about XZMDKVG55W-7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com