

Y0007109R740B9L

Quote

Y0007109R740B9L Information

	Part Number	Y0007109R740B9L	
Contact larves state two	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
	Category	Resistors Through Hole Resistors	
	Description	RES 109.74 OHM 0.6W 0.1% RADIAL	
	Package	Radial	1177
For Reference Only		For the pricing/inventory/lead time, please contact	
		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a (

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y0007109R740B9L Specifications

Manufacturer Part NumberY0007109R740B9LManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryRobitsPackageThrough Hole ResistorsSeriesRadialSeries0.974 OhmsTolerance40.1%Power (Watts)0.6WCompositionMatal FoilFeaturesMoisture Resistant, Non-InductivePackage / CaseSoft C ~ 125°CSupplier Device Package-Size / Dimension0.300° L x 0.105° W (7.62mm x 2.67mm)Height - Seated (Max)0.336° (8.53mm)Number of Terminations2Serier Rate-Serier Rate-Start Part Part Rate-Start Part Part Rate-Start Part Part Part Part Part Part Part			
CategoryResistorsPackageRadialPackageRadialSeriesSResistance109.74 OhmsTolerance±0.1%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.330° L x 0.105° W (7.62mm x 2.67mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer Part Number	Y0007109R740B9L	
FunctionThrough Hole ResistorsPackageRadialSeriesSResistance109.74 OhmsTolerance±0.1%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperature Coefficient±2ppm°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Pailure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
PackageRadialSeriesSResistance109.74 OhmsTolerance±0.1%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Feight - Seated (Max)0.300" L x 0.105" W (7.62mm x 2.67mm)Number of Terminations2Failure Rate-	Category	Resistors	
SeriesSResistance109.74 OhmsTolerance±0.1%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package.Feight - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate.		Through Hole Resistors	
Resistance109.74 OhmsTolerance±0.1%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Pailure Rate-Failure Rate-	Package	Radial	
Tolerance±0.1%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package.Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Number of Terminations2Failure Rate.	Series	S	
Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Resistance	109.74 Ohms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient $\pm 2ppm^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Package / CaseRadialSupplier Device Package-Size / Dimension $0.300^{\circ}L x \ 0.105^{\circ}W \ (7.62mm x \ 2.67mm)$ Height - Seated (Max) $0.336^{\circ}(8.53mm)$ Number of Terminations 2 Failure Rate-	Tolerance	$\pm 0.1\%$	
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Power (Watts)	0.6W	
Temperature Coefficient±2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Composition	Metal Foil	
Operating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Features	Moisture Resistant, Non-Inductive	
Package / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±2ppm/°C	
Supplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension 0.300" L x 0.105" W (7.62mm x 2.67mm) Height - Seated (Max) 0.336" (8.53mm) Number of Terminations 2 Failure Rate -	Package / Case	Radial	
Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Supplier Device Package	-	
Number of Terminations2Failure Rate-	Size / Dimension	0.300" L x 0.105" W (7.62mm x 2.67mm)	
Failure Rate -	Height - Seated (Max)	0.336" (8.53mm)	
	Number of Terminations	2	
Report error	Failure Rate	-	
Report end		Report errors?	

Y0007109R740B9L Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y0007109R740B9L Payment Methods



If you have any question about Y0007109R740B9L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com