

Y11722K47000B9R

Quote

Y11722K47000B9R Information

	Part Number	Y11722K47000B9R	
	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	回約28
Contraction of the second seco	Category	Resistors Chip Resistor - Surface Mount	
	Description	RES SMD 2.47KOHM 0.1% 1/10W 0805	S¥≇
	Package	0805 (2012 Metric)	- INX-3
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y11722K47000B9R Specifications

Manufacturer Part Number Y11722K47000B9R Manufacturer Vishay Foil Resistors (Division of Vishay Precision Group) Category Resistors Chip Resistor - Surface Mount Chip Resistor - Surface Mount Package 0805 (2012 Metric) Series VSM Resistance 2.47 kOhms Tolerance 40.1% Power (Watts) 0.1W, 1/10W Composition Metal Foil Features Moisture Resistant, Non-Inductive Tolerance coefficient ±2ppm/°C Operating Temperature -55°C ~ 150°C Step / Case 0805 (2012 Metric) Supplier Device Package 0805 (2012 Metric) Size / Dimension 0.080° L x 0.050° W (2.03mm x 1.27mm) Height - Seated (Max) 0.025° (0.64mm) Number of Terminations 2 Failure Rate -			
CategoryResistorsChip Resistor - Surface MountPackage0805 (2012 Metric)SeriesVSMResistance2.47 kOhmsTolerance±0.1%Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm°COperating Temperature-55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0.800° L x 0.050° W (2.03mm x 1.27mm)Height - Seated (Max)0.25° (0.64mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	Y11722K47000B9R	
Initial Chip Resistor - Surface MountPackage0805 (2012 Metric)SeriesVSMResistance2.47 kOhmsTolerance±0.1%Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature.55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0.080° L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate.	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
Package0805 (2012 Metric)SeriesVSMResistance2.47 kOhmsTolerance±0.1%Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperating Temperature±2ppm/°COperating Temperature0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-	Category	Resistors	
SeriesVSMResistance2.47 kOhmsTolerance±0.1%Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0.080° L x 0.050° W (2.03mm x 1.27mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount	
Resistance2.47 kOhmsTolerance±0.1%Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CSupplier Device Package8005Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2Failure Rate-	Package	0805 (2012 Metric)	
Tolerance±0.1%Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm°COperating Temperaturee55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Series	VSM	
Power (Watts)0.1W, 1/10WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Resistance	2.47 kOhms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.1\%$	
FeaturesMoisture Resistant, Non-InductiveFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient $\pm 2ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 150^{\circ}C$ Package / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Power (Watts)	0.1W, 1/10W	
Temperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Composition	Metal Foil	
Operating Temperature -55°C ~ 150°C Package / Case 0805 (2012 Metric) Supplier Device Package 0805 Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Features	Moisture Resistant, Non-Inductive	
Package / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±2ppm/°C	
Supplier Device Package 0805 Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 150°C	
Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Package / Case	0805 (2012 Metric)	
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Supplier Device Package	0805	
Number of Terminations2Failure Rate-	Size / Dimension	0.080" L x 0.050" W (2.03mm x 1.27mm)	
Failure Rate -	Height - Seated (Max)	0.025" (0.64mm)	
	Number of Terminations	2	
Report errors?	Failure Rate	-	
•		Report errors?	

Y11722K47000B9R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y11722K47000B9R Payment Methods





If you have any question about Y11722K47000B9R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com