

# Y1453111R670V9L

## Y1453111R670V9L Information



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## Y1453111R670V9L Specifications

Manufacturer Part NumberY1453111R670V9LManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryRobitsPackageRadialSeriesZResistance111.67 OhmsTolerance±0.005%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePackage / CaseRadialSpelier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Stated (Max)2Number of Terminations2Feature Rate-		
CategoryResistorsPackageRadialPackageRadialSeriesZResistance111.67 OhmsTolerance±0.005%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer Part Number	Y1453111R670V9L
FunctionThrough Hole ResistorsPackageRadialSeriesZResistance111.67 OhmsTolerance±0.005%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Pailure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)
PackageRadialSeriesZResistance111.67 OhmsTolerance±0.005%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Feight - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Category	Resistors
SeriesZResistance111.67 OhmsTolerance±0.005%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Through Hole Resistors
Resistance III.67 Ohms   Tolerance ±0.005%   Power (Watts) 0.6W   Composition Metal Foil   Features Moisture Resistant, Non-Inductive   Temperature Coefficient ±0.2ppm/°C   Operating Temperature -55°C ~ 125°C   Package / Case Radial   Supplier Device Package -   Size / Dimension 0.300" L x 0.105" W (7.62mm x 2.67mm)   Height - Seated (Max) 0.336" (8.53mm)   Number of Terminations 2   Failure Rate -	Package	Radial
Tolerance±0.005%Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package.Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate.	Series	Z
Power (Watts)0.6WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0Number of Terminations2Failure Rate-	Resistance	111.67 Ohms
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient $\pm 0.2 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Package / CaseRadialSupplier Device Package-Size / Dimension $0.300^{\circ}L x \ 0.105^{\circ}W \ (7.62 mm x \ 2.67 mm)$ Height - Seated (Max) $2$ Number of Terminations $2$ Failure Rate-	Tolerance	$\pm 0.005\%$
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Power (Watts)	0.6W
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Composition	Metal Foil
Operating Temperature-55°C ~ 125°CPackage / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Features	Moisture Resistant, Non-Inductive
Package / CaseRadialSupplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±0.2ppm/°C
Supplier Device Package-Size / Dimension0.300" L x 0.105" W (7.62mm x 2.67mm)Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.300" L x 0.105" W (7.62mm x 2.67mm)   Height - Seated (Max) 0.336" (8.53mm)   Number of Terminations 2   Failure Rate -	Package / Case	Radial
Height - Seated (Max)0.336" (8.53mm)Number of Terminations2Failure Rate-	Supplier Device Package	-
Number of Terminations2Failure Rate-	Size / Dimension	0.300" L x 0.105" W (7.62mm x 2.67mm)
Failure Rate -	Height - Seated (Max)	0.336" (8.53mm)
	Number of Terminations	2
Report errors	Failure Rate	-
		Report errors?

#### Y1453111R670V9L Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### Y1453111R670V9L Payment Methods





If you have any question about Y1453111R670V9L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com