

Y145510K0000T0W

Y145510K0000T0W Information

| | Part Number | Y145510K0000T0W | |
|----------------------------|--------------|---|--|
| Contact service statutions | Manufacturer | Vishay Foil Resistors (Division of Vishay Precision Group) | |
| | Category | Resistors Chip Resistor - Surface Mount | |
| | Description | RES SMD 10K OHM 0.01% 1/5W 1506 | 11 A A A A A A A A A A A A A A A A A A |
| | Package | 1506 | 同じいを見て |
| For Reference Only | | For the pricing/inventory/lead time, please contact | |
| | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y145510K0000T0W Specifications

| Manufacturer Part NumberY145510K0000T0WManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryRoistorsPackage1506SeriesVSMResistance10 kOhmsTolerance4.01%Power (Watts)0.2W, 1/SWCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoregrature Coefficient±2ppm°COperating Temperature1506Supplier Device Package1506Size / Dimension150°Number of Terminations2Aumer of Terminations2Number of Terminations2 <tr< th=""><th></th><th></th></tr<> | | | |
|---|--------------------------|--|--|
| CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMResistance10 kOhmsTolerance±0.01%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature55°C ~ 150°CSupplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.2S" (0.64mm)Number of Terminations2Failure Rate- | Manufacturer Part Number | Y145510K0000T0W | |
| Chip Resistor - Surface MountPackage1506SeriesVSMResistance10 kOhmsTolerance±0.01%Power (Watts)0.2W, 1/SWCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150° L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)2Number of Terminations2Failure Rate- | Manufacturer | Vishay Foil Resistors (Division of Vishay Precision Group) | |
| Package 1506 Series VSM Resistance 10 kOhms Tolerance ±0.01% Power (Watts) 0.2W, 1/5W Composition Metal Foil Features Moisture Resistant, Non-Inductive Temperature Coefficient ±2ppm/°C Operating Temperature -55°C ~ 150°C Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate - | Category | Resistors | |
| SeriesVSMResistance10 kOhmsTolerance±0.01%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2pm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2Failure Rate- | | Chip Resistor - Surface Mount | |
| Resistance10 kOhmsTolerance±0.01%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55° C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.025" (0.64mm) x 1.57mm)Height - Seated (Max)2Pailure Rate- | Package | 1506 | |
| Tolerance±0.01%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Series | VSM | |
| Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Resistance | 10 kOhms | |
| CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Tolerance | $\pm 0.01\%$ | |
| FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Power (Watts) | 0.2W, 1/5W | |
| Temperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Composition | Metal Foil | |
| Operating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Features | Moisture Resistant, Non-Inductive | |
| Package / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Temperature Coefficient | ±2ppm/°C | |
| Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Operating Temperature | -55°C ~ 150°C | |
| Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Package / Case | 1506 | |
| Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate- | Supplier Device Package | 1506 | |
| Number of Terminations 2 Failure Rate - | Size / Dimension | 0.150" L x 0.062" W (3.81mm x 1.57mm) | |
| Failure Rate - | Height - Seated (Max) | 0.025" (0.64mm) | |
| | Number of Terminations | 2 | |
| | Failure Rate | - | |
| Report error | | Report errors? | |

Y145510K0000T0W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y145510K0000T0W Payment Methods



If you have any question about Y145510K0000T0W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com