

Y14553K72000B0R

Quote

Y14553K72000B0R Information

	Part Number	Y14553K72000B0R	
	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	I I 565
Containance cantener	Category	Resistors Chip Resistor - Surface Mount	
	Description	RES SMD 3.72K OHM 0.1% 1/5W 1506	- 59672
	Package	1506	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y14553K72000B0R Specifications

Manufacturer Part NumberY14553K72000B0RManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryResistorsPackageChip Resistor - Surface MountPackage1506SeriesVSMResistance3.72 kOhmsTolerancee0.1%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePackage / Case5.5°C ~ 150°CSylpier Device Package1506Size / Dimension0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-			
CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMResistance3.72 kOhmsTolerance±0.1%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature55°C ~ 150°CSupplier Device Package1506Size / Dimension0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.2Number of Terminations2Failure Rate-	Manufacturer Part Number	Y14553K72000B0R	
Chip Resistor - Surface MountPackage1506SeriesVSMResistance3.72 kOhmsTolerance±0.1%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperature Coefficient±2ppm/°COperating Temperature1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
Package106SeriesVSMResistance3.72 kOhmsTolerance±0.1%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature.55°C ~ 150°CPackage / Case1506Supplier Device Package0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.22s" (0.64mm)Number of Terminations2Failure Rate.	Category	Resistors	
SeriesVSMResistance3.72 kOhmsTolerance±0.1%Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount	
Resistance3.72 kOhmsTolerance±0.1%Power (Wats)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Package	1506	
Tolerance±0.1%Power (Watts)0.2W, 1/SWCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150°L x 0.062°W (3.81mm x 1.57mm)Height - Seated (Max)0.25° (0.64mm)Number of Terminations2Failure Rate-	Series	VSM	
Power (Watts)0.2W, 1/5WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Resistance	3.72 kOhms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.1\%$	
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Power (Watts)	0.2W, 1/5W	
Temperature Coefficient±2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Composition	Metal Foil	
Operating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Features	Moisture Resistant, Non-Inductive	
Package / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±2ppm/°C	
Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Operating Temperature	$-55^{\circ}C \sim 150^{\circ}C$	
Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Package / Case	1506	
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Supplier Device Package	1506	
Number of Terminations 2 Failure Rate -	Size / Dimension	0.150" L x 0.062" W (3.81mm x 1.57mm)	
Failure Rate -	Height - Seated (Max)	0.025" (0.64mm)	
	Number of Terminations	2	
Report error	Failure Rate	-	
Report end		Report errors?	

Y14553K72000B0R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y14553K72000B0R Payment Methods





If you have any question about Y14553K72000B0R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com