

Y1622100R000B9L

Y1622100R000B9L Information

Heisener.com	Manufacturar	Y1622100R000B9L Vishay Foil Resistors (Division of Vishay Precision Group) Resistors Through Hole Resistors RES 100 OHM 8W 0.1% TO220-2 TO-220-2	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y1622100R000B9L Specifications

Manufacturer Part NumberY1622100R000B9LManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageTO-220-2SeriesVPR220ZResistance100 OhmsTolerance±0.1%Power (Watts)8WCompositionMatal FoilFeaturesMoisture Resistant, Non-InductivePoregrature Coefficient±0.220-2Supplier Device PackageTO-220-2Size / Dimension6.400° L x 0.150° W (10.16mm x 3.81mm)Height - Seated (Max)2Number of Terminations2Number of Terminations2Number of Terminations2Number of Terminations10Number of			
CategoryResistorsThrough Hole ResistorsPackageTO-220-2SeriesVPR220ZResistance100 OhmsTolerance±0.1%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CSupplier Device PackageTO-220-2Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	Y1622100R000B9L	
Hough Hole ResistorsPackageTO-220-2SeriesVPR20ZResistance100 OhmsTolerance±0.1%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / CaseTO-220-2Supplier Device Package0.400° L x 0.150° W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
PackageTO-20-2SeriesVPR220ZResistance100 OhmsTolerance±0.1%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Category	Resistors	
SeriesVPR220ZSeries100 OhmsResistance100 OhmsTolerance±0.1%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-		Through Hole Resistors	
Resistance100 OhmsTolerance±0.1%Power (Wats)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Package	TO-220-2	
Tolerance±0.1%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Series	VPR220Z	
Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Resistance	100 Ohms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.1\%$	
FeaturesMoisture Resistant, Non-InductiveFeatures±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Power (Watts)	8W	
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Composition	Metal Foil	
Operating Temperature-55°C ~ 150°CPackage / CaseTO-220-2Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Features	Moisture Resistant, Non-Inductive	
Package / CaseTO-220-2Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±0.2ppm/°C	
Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 150°C	
Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.845" (21.46mm) Number of Terminations 2 Failure Rate -	Package / Case	TO-220-2	
Height - Seated (Max)0.845" (21.46mm)Number of Terminations2Failure Rate-	Supplier Device Package	TO-220	
Number of Terminations2Failure Rate-	Size / Dimension	0.400" L x 0.150" W (10.16mm x 3.81mm)	
Failure Rate -	Height - Seated (Max)	0.845" (21.46mm)	
	Number of Terminations	2	
	Failure Rate	-	
Report errors		Report errors?	

Y1622100R000B9L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y1622100R000B9L Payment Methods





If you have any question about Y1622100R000B9L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com