

Y162610K0000T0W

Juote

Y162610K0000T0W Information

Heisener.com	Part Number	Y162610K0000T0W	
	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
	Category	Resistors Chip Resistor - Surface Mount	
	Description	RES SMD 10K OHM 0.01% 0.3W 1506	- 2587233
	Package	1506	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us	
		Website: https://www.heisener.com	Request a Qu
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y162610K0000T0W Specifications

Manufacturer Part NumberY162610K0000T0WManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMPResistance10 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeatures10.02pm/°COperating Temperature.55°C ~ 150°COperating Temperature1506Supplier Device Package1506Size / Dimension0.150° L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)0.25° (0.64mm)Number of Terminations2Failure Rate.			
CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMPResistance10 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Number of Terminations2	Manufacturer Part Number	Y162610K0000T0W	
Chip Resistor - Surface MountPackage1506SeriesVSMPResistance10 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
Package10SeriesVSMPResistance10 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)2	Category	Resistors	
SeriesVSMPResistance10 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2		Chip Resistor - Surface Mount	
Resistance10 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Package	1506	
Tolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package0.150° L x 0.062″ W (3.81mm x 1.57mm)Height - Seated (Max)0.25″ (0.64mm)Number of Terminations2	Series	VSMP	
Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Resistance	10 kOhms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Tolerance	$\pm 0.01\%$	
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Power (Watts)	0.3W	
Temperature Coefficient ±0.2ppm/°C Operating Temperature -55° C ~ 150° C Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Composition	Metal Foil	
Operating Temperature -55°C ~ 150°C Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Features	Moisture Resistant, Non-Inductive	
Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Temperature Coefficient	±0.2ppm/°C	
Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Operating Temperature	-55°C ~ 150°C	
Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Package / Case	1506	
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Supplier Device Package	1506	
Number of Terminations 2	Size / Dimension	0.150" L x 0.062" W (3.81mm x 1.57mm)	
	Height - Seated (Max)	0.025" (0.64mm)	
Failure Rate -	Number of Terminations	2	
	Failure Rate	-	
Report er		Report errors?	

Y162610K0000T0W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y162610K0000T0W Payment Methods



If you have any question about Y162610K0000T0W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com