

Y1626110R000Q9R

Y1626110R000Q9R Information

Heisener.com	Part Number Manufacturer Category Description Package	Y1626110R000Q9R Vishay Foil Resistors (Division of Vishay Precision Group) Resistors Chip Resistor - Surface Mount RES SMD 110 OHM 0.02% 0.3W 1506 1506	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y1626110R000Q9R Specifications

Manufacturer Part NumberY1626110R000Q9RManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsPackageChip Resistor - Surface MountPackage1506SeriesVSMPResistance110 OhmsTolerance±0.02%Power (Wats)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePenetarer±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150° L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)0.225° (0.64mm)Number of Terminations2Failure Rate-			
CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMPResistance110 OhmsTolerance±0.02%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Number of Terminations2	Manufacturer Part Number	Y1626110R000Q9R	
Chip Resistor - Surface MountPackage1506SeriesVSMPResistance110 OhmsTolerance±0.02%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
Package100SeriesVSMPResistance110 OhmsTolerance±0.02%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2	Category	Resistors	
SeriesVSMPResistance110 OhmsTolerance±0.02%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2		Chip Resistor - Surface Mount	
Resistance110 OhmsTolerance±0.02%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2	Package	1506	
Tolerance±0.02%Power (Wats)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150°L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2	Series	VSMP	
Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Resistance	110 Ohms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Tolerance	±0.02%	
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Power (Watts)	0.3W	
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Composition	Metal Foil	
Operating Temperature -55°C ~ 150°C Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Features	Moisture Resistant, Non-Inductive	
Package / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Temperature Coefficient	±0.2ppm/°C	
Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Operating Temperature	$-55^{\circ}C \sim 150^{\circ}C$	
Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Package / Case	1506	
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Supplier Device Package	1506	
Number of Terminations 2	Size / Dimension	0.150" L x 0.062" W (3.81mm x 1.57mm)	
	Height - Seated (Max)	0.025" (0.64mm)	
Failure Rate	Number of Terminations	2	
	Failure Rate	-	
Report e		Report errors?	

Y1626110R000Q9R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y1626110R000Q9R Payment Methods





If you have any question about Y1626110R000Q9R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com