

Y162636R5000C0R

a Quote

Y162636R5000C0R Information

	Part Number	Y162636R5000C0R	
Heisener.com	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	∎S3
	Category	Resistors Chip Resistor - Surface Mount	
	Description	RES SMD 36.5 OHM 0.25% 0.3W 1506	- 200
	Package	1506	I
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y162636R5000C0R Specifications

Manufacturer Part NumberY162636R5000C0RManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryResistorsPackage1506SeriesVSMPResistance36.5 OhmsTolerance40.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePackage / Case50°C ~ 150°COperating Temperature50°C ~ 150°CSize / Dimension1.50°L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)0.225° (0.64mm)Number of Terminations2Package / Case0.25%Fight rest0.25% (0.64mm)Size / Dimension0.25°C (0.64mm)Size / Dimension0.25°C (0.64mm)Number of Terminations2Package / Case1.50°C (0.64mm)Size / Dimension0.25°C (0.64mm)Size / Dimension2Size / Dimension1.50°C (0.64mm)Size / Dimension2Size / Dimension2Size / Dimension2Size / Dimension2Size / Dimension3Size / Dimens				
CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMPResistance36.5 OhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CSupplier Device Package1506Size / Dimension0.150° L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)0.25° (0.64mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	Y162636R5000C0R		
Chip Resistor - Surface MountPackage1506SeriesVSMPResistance36.5 OhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150° L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)		
Package1506SeriesVSMPResistance36.5 OhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)2Pailure Rate-	Category	Resistors		
SeriesVSMPResistance36.5 OhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount		
Resistance36.5 OhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150° L x 0.062″ W (3.81mm x 1.57mm)Height - Seated (Max)0.025″ (0.64mm)Number of Terminations2Failure Rate-	Package	1506		
Tolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Series	VSMP		
Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81 mm x 1.57 mm)Height - Seated (Max)0.025" (0.64 mm)Number of Terminations2Failure Rate-	Resistance	36.5 Ohms		
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Tolerance	±0.25%		
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Power (Watts)	0.3W		
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Composition	Metal Foil		
Operating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Features	Moisture Resistant, Non-Inductive		
Package / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±0.2ppm/°C		
Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 150°C		
Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Package / Case	1506		
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Supplier Device Package	1506		
Number of Terminations2Failure Rate-	Size / Dimension	0.150" L x 0.062" W (3.81mm x 1.57mm)		
Failure Rate -	Height - Seated (Max)	0.025" (0.64mm)		
	Number of Terminations	2		
Report error	Failure Rate	-		
Report choir		Report errors?		

Y162636R5000C0R Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y162636R5000C0R Payment Methods





If you have any question about Y162636R5000C0R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com