

Y16265K00000T9W

Quote

Y16265K00000T9W Information

Contraction terr	Part Number	Y16265K00000T9W	
	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	•
	Category	Resistors Chip Resistor - Surface Mount	
	Description	RES SMD 5K OHM 0.01% 0.3W 1506	
	Package	1506	- 国際報告
For Reference Only		For the pricing/inventory/lead time, please contact	
		us	
		Website: https://www.heisener.com	Request a
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y16265K00000T9W Specifications

Manufacturer Part NumberY16265K0000T9WManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryChip Resistor - Surface MountPackage1506SoriesVSMPResistance5 kohmsTolerance4.0.01%Power (Watts)0.3WCompositionMatle FoilFeaturesMoisture Resistant, Non-InductivePoreating Temperature5.5°C ~ 150°COperating Temperature1506Supplier Device Package1506Size / Dimension0.150° L x 0.062° W (3.81mm x 1.57mm)Height - Seated (Max)0Number of Terminations2Failure Rate-			
CategoryResistorsChip Resistor - Surface MountPackage1506SeriesVSMPResistance5 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)2	Manufacturer Part Number	Y16265K00000T9W	
Chip Resistor - Surface MountPackage1506SeriesVSMPResistance5 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0Number of Terminations2	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)	
Package106SeriesVSMPResistance5 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperature Coefficient±0.2ppm/°COperating Temperature55°C ~ 150°CPackage / Case1506Supplier Device Package0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.25" (0.64mm)Number of Terminations2	Category	Resistors	
SeriesVSMPResistance5 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2		Chip Resistor - Surface Mount	
Resistance5 kOhmsTolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package0.150° L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)2	Package	1506	
Tolerance±0.01%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0Number of Terminations2	Series	VSMP	
Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Resistance	5 kOhms	
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient $\pm 0.2 ppm^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 150^{\circ}C$ Package / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81 mm x 1.57 mm)Height - Seated (Max)0.025" (0.64 mm)Number of Terminations2	Tolerance	$\pm 0.01\%$	
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1506Supplier Device Package1506Size / Dimension0.150" L x 0.062" W (3.81mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Power (Watts)	0.3W	
Temperature Coefficient ±0.2ppm/°C Operating Temperature -55°C ~ 150°C Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Composition	Metal Foil	
Operating Temperature -55°C ~ 150°C Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Features	Moisture Resistant, Non-Inductive	
Package / Case 1506 Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Temperature Coefficient	±0.2ppm/°C	
Supplier Device Package 1506 Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Operating Temperature	-55°C ~ 150°C	
Size / Dimension 0.150" L x 0.062" W (3.81mm x 1.57mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2	Package / Case	1506	
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2	Supplier Device Package	1506	
Number of Terminations 2	Size / Dimension	0.150" L x 0.062" W (3.81mm x 1.57mm)	
	Height - Seated (Max)	0.025" (0.64mm)	
Failure Rate -	Number of Terminations	2	
	Failure Rate	-	
Report err		Report errors?	

Y16265K00000T9W Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y16265K00000T9W Payment Methods



If you have any question about Y16265K00000T9W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com