

# Y163010K4000T9W

## Y163010K4000T9W Information

		Part Number	Y163010K4000T9W Vishay Foil Resistors (Division of Vishay Precision	
		Manufacturer	Group)	
	www.heisener.com	Category	Resistors Chip Resistor - Surface Mount	10.25
		Description	RES SMD 10.4KOHM 0.01% 1/4W 1206	246 344
		Package	1206 (3216 Metric)	回深武派
			For the pricing/inventory/lead time, please contact us	
	For Reference Only		Website: https://www.heisener.com	Request a Quote
L			E-mail: salesdept@heisener.com	

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# Y163010K4000T9W Specifications

Manufacturer Part NumberY163010K4000T9WManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)SeriesVFCPResistance10.4 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature.55°C ~ 150°CPackage / Case1206 (3216 Metric)
CategoryResistorsCategoryResistor - Surface MountPackage1206 (3216 Metric)Package1206 (3216 Metric)SeriesVFCPResistance10.4 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
ChingeryChinePackage1206 (3216 Metric)SeriesVFCPResistance10.4 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
Package1206 (3216 Metric)SeriesVFCPResistance10.4 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
SeriesVFCPResistance10.4 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature-55°C ~ 150°C
Resistance10.4 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
Tolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
CompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
FeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°C
Operating Temperature $-55^{\circ}C \sim 150^{\circ}C$
Package / Case 1206 (3216 Metric)
Supplier Device Package 1206
Size / Dimension 0.126" L x 0.062" W (3.20mm x 1.57mm)
Height - Seated (Max) 0.025" (0.64mm)
Number of Terminations 2
Failure Rate -
Report en

#### Y163010K4000T9W Guarantees



Quality Guarantees


We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## Y163010K4000T9W Payment Methods



If you have any question about Y163010K4000T9W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com