

Y163022K6000T9W

Y163022K6000T9W Information

www.heisener.com	Part Number Manufacturer Category Description	Y163022K6000T9W Vishay Foil Resistors (Division of Vishay Precision Group) Resistors Chip Resistor - Surface Mount RES SMD 22.6KOHM 0.01% 1/4W 1206	
	Package	1206 (3216 Metric)	
For Reference Only		For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y163022K6000T9W Specifications

Manufacturer Part NumberY163022K6000T9WManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsCategoryResistorsPackage1206 (3216 Metric)Package226 KOhmsSeriesVFCPResistance22.6 KOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)Height - Seated (Max)0.025" (0.64mm)		
CategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)SeriesVFCPResistance22.6 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1206Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Chip Resistor - Surface MountPackage1206 (3216 Metric)SeriesVFCPResistance22.6 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm°COperating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)	Vishay Foil Resistors (Division of Vishay Precision Group)	
Package1206 (3216 Metric)SeriesVFCPResistance22.6 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Series VFCP Resistance 22.6 kOhms Tolerance ±0.01% Power (Watts) 0.25W, 1/4W Composition Metal Foil Features Anti-Sulfur, Moisture Resistant, Non-Inductive Temperature Coefficient ±0.2ppm/°C Operating Temperature 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.062" W (3.20mm x 1.57mm)		
Resistance22.6 kOhmsTolerance±0.01%Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Tolerance ±0.01% Power (Watts) 0.25W, 1/4W Composition Metal Foil Features Anti-Sulfur, Moisture Resistant, Non-Inductive Temperature Coefficient ±0.2pm/°C Operating Temperature -55°C ~ 150°C Package / Case 1206 (3216 Metric) Supplier Device Package 0.126°L x 0.062°W (3.20mm x 1.57mm)		
Power (Watts)0.25W, 1/4WCompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
CompositionMetal FoilFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
FeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Operating Temperature-55°C ~ 150°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Supplier Device Package1206Size / Dimension0.126" L x 0.062" W (3.20mm x 1.57mm)		
Size / Dimension 0.126" L x 0.062" W (3.20mm x 1.57mm)		
Height - Seated (Max) 0.025" (0.64mm)		
Number of Terminations 2		
Failure Rate -		
Rep	ort errors?	

Y163022K6000T9W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y163022K6000T9W Payment Methods



If you have any question about Y163022K6000T9W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com