

Y16901R50000Q0L

Y16901R50000Q0L Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y16901R50000Q0L Specifications

Manufacturer Part NumberY16901R5000Q0LManufacturerVishay Foil Resistors (Division of Vishay Precision Group)CategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageT0-220-4SeriesVPR221ZResistance1.5 OhmsTolerance40.02%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveOperating Temperature55°C ~ 150°CPackage / CaseT0-220.4Supplier Device PackageT0-220.4Size / Dimension0.400° L x 0.150° W (10.16mm x 3.81mm)Height - Seated (Max)0.845° (21.46mm)Number of Terminations4Aure Marcure Marcure And Marcure		
CategoryResistorsThrough Hole ResistorsPackageTO-220-4SeriesVPR221ZResistance1.5 OhmsTolerance±0.02%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CSupplier Device PackageTO-220Size / Dimension0.400° L x 0.150° W (10.16mm x 3.81mm)Height - Seated (Max)0.845° (21.46mm)Number of Terminations4Failure Rate.	Manufacturer Part Number	Y16901R50000Q0L
Through Hole ResistorsPackageTO-220-4SeriesVPR221ZResistance1.5 OhmsTolerance±0.02%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperature Coefficient±0.2pm/°COperating Temperature55°C ~ 150°CPackage / CaseTO-220-4Supplier Device Package0.400° L x 0.150° W (10.16mm x 3.81mm)Height - Seated (Max)4Failure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)
Package TO-20-4 Series VPR221Z Resistance 1.5 Ohms Tolerance ±0.02% Power (Watts) 8W Composition Metal Foil Features Moisture Resistant, Non-Inductive Temperature Coefficient ±0.2pm/°C Operating Temperature -55°C ~ 150°C Package / Case TO-220-4 Supplier Device Package TO-220 Size / Dimension 0.400° L x 0.150° W (10.16mm x 3.81mm) Height - Seated (Max) 0.845° (21.46mm) Number of Terminations 4	Category	Resistors
SeriesVPR221ZResistance1.5 OhmsTolerance±0.02%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2pm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-2204Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-		Through Hole Resistors
Resistance1.5 OhmsTolerance±0.02%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Package	TO-220-4
Tolerance±0.02%Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device Package0.400° L x 0.150° W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Series	VPR221Z
Power (Watts)8WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device Package0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Resistance	1.5 Ohms
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Tolerance	$\pm 0.02\%$
FeaturesMoisture Resistant, Non-InductiveFeatures±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Power (Watts)	8W
Temperature Coefficient±0.2ppm/°COperating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Composition	Metal Foil
Operating Temperature-55°C ~ 150°CPackage / CaseTO-220-4Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Features	Moisture Resistant, Non-Inductive
Package / CaseTO-220-4Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Temperature Coefficient	±0.2ppm/°C
Supplier Device PackageTO-220Size / Dimension0.400" L x 0.150" W (10.16mm x 3.81mm)Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Operating Temperature	-55°C ~ 150°C
Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.845" (21.46mm) Number of Terminations 4 Failure Rate -	Package / Case	TO-220-4
Height - Seated (Max)0.845" (21.46mm)Number of Terminations4Failure Rate-	Supplier Device Package	TO-220
Number of Terminations4Failure Rate-	Size / Dimension	0.400" L x 0.150" W (10.16mm x 3.81mm)
Failure Rate -	Height - Seated (Max)	0.845" (21.46mm)
	Number of Terminations	4
Papert arro	Failure Rate	-
Keport eno		Report errors?

Y16901R50000Q0L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y16901R50000Q0L Payment Methods





If you have any question about Y16901R50000Q0L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com