

Y40622K60000C0W

Y40622K60000C0W Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Y40622K60000C0W Specifications

Manufacturer Part Number Y40622K60000C0W Manufacturer Vishay Foil Resistors (Division of Vishay Precision Group) Category Resistors Chip Resistor - Surface Mount Package 0805 (2012 Metric) Series FRSH Resistance 2.6 kOhms Tolerance ±0.25% Power (Watts) 0.3W Composition Metal Foil Features Moisture Resistant, Non-Inductive Tolerance coefficient ±2.5ppm/°C Operating Temperature 65°C ~ 225°C Package / Case 0805 (2012 Metric) Size / Dimension 0.080° L x 0.050° W (2.03mm x 1.27mm) Height - Seated (Max) 0.025° (0.64mm) Number of Terminations 2 Failure Rate -		
CategoryResistorsChip Resistor - Surface MountPackage0805 (2012 Metric)SeriesFRSHResistance2.6 kOhms10erance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5pm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0.800° L x 0.050° W (2.03mm x 1.27mm)Height - Seated (Max)0.025° (0.64mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	Y40622K60000C0W
Initial Chip Resistor - Surface MountPackage0805 (2012 Metric)SeriesFRSHResistance2.6 kOhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperating Temperature±.5spm/°COperating Temperature0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-	Manufacturer	Vishay Foil Resistors (Division of Vishay Precision Group)
Package0805 (2012 Metric)SeriesFRSHResistance2.6 kOhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductivePoperating Temperature±2.5ppm/°COperating Temperature0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.025" (0.64mm)Height - Seated (Max)2Failure Rate-	Category	Resistors
SeriesFRSHResistance2.6 kOhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5ppm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0.080° L x 0.050° W (2.03mm x 1.27mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount
Resistance2.6 kOhmsTolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5ppm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0.800° L x 0.050° W (2.03mm x 1.27mm)Height - Seated (Max)0.25° (0.64mm)Number of Terminations2Failure Rate-	Package	0805 (2012 Metric)
Tolerance±0.25%Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5pm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0.805" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Series	FRSH
Power (Watts)0.3WCompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5ppm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Resistance	2.6 kOhms
CompositionMetal FoilFeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5ppm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Tolerance	±0.25%
FeaturesMoisture Resistant, Non-InductiveTemperature Coefficient±2.5ppm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Power (Watts)	0.3W
Temperature Coefficient±2.5ppm/°COperating Temperature-55°C ~ 225°CPackage / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Composition	Metal Foil
Operating Temperature -55°C ~ 225°C Package / Case 0805 (2012 Metric) Supplier Device Package 0805 Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Features	Moisture Resistant, Non-Inductive
Package / Case0805 (2012 Metric)Supplier Device Package0805Size / Dimension0.080" L x 0.050" W (2.03mm x 1.27mm)Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±2.5ppm/°C
Supplier Device Package 0805 Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 225°C
Size / Dimension 0.080" L x 0.050" W (2.03mm x 1.27mm) Height - Seated (Max) 0.025" (0.64mm) Number of Terminations 2 Failure Rate -	Package / Case	0805 (2012 Metric)
Height - Seated (Max)0.025" (0.64mm)Number of Terminations2Failure Rate-	Supplier Device Package	0805
Number of Terminations2Failure Rate-	Size / Dimension	0.080" L x 0.050" W (2.03mm x 1.27mm)
Failure Rate -	Height - Seated (Max)	0.025" (0.64mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
•		Report errors?

Y40622K60000C0W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

Y40622K60000C0W Payment Methods



If you have any question about Y40622K60000C0W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com