



YC324-JK-0722KL Information

Part Number YC324-JK-0722KL

Manufacturer Yageo **Category** Resistors

Resistor Networks, Arrays

DescriptionRES ARRAY 4 RES 22K OHM 2012**Package**2012, Convex, Long Side Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









YC324-JK-0722KL Specifications

ManufacturerYageoCategoryResistorsResistor Networks, ArraysPackage2012, Convex, Long Side TerminalsSeriesYC324Circuit TypeIsolatedResistance (Ohms)22kTolerance±5%Number of Resistors4Number of Pins8Power Per Element125mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface Mount		
Category Resistor Networks, Arrays Package 2012, Convex, Long Side Terminals Series YC324 Circuit Type Isolated Resistance (Ohms) 22k Tolerance ±5% Number of Resistors 4 Number of Pins 8 Power Per Element 125mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount	Manufacturer Part Number	YC324-JK-0722KL
Resistor Networks, Arrays Package 2012, Convex, Long Side Terminals Series YC324 Circuit Type Isolated Resistance (Ohms) 22k Tolerance ±5% Number of Resistors 4 Number of Pins 8 Power Per Element 125mW Temperature Coefficient 220ppm/°C Operating Temperature -55°C ~ 155°C Applications Mounting Type Surface Mount	Manufacturer	Yageo
Package2012, Convex, Long Side TerminalsSeriesYC324Circuit TypeIsolatedResistance (Ohms)22kTolerance±5%Number of Resistors4Number of Pins8Power Per Element125mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface Mount	Category	Resistors
Series YC324 Circuit Type Isolated Resistance (Ohms) 22k Tolerance ±5% Number of Resistors 4 Number of Pins 8 Power Per Element 125mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 22k Tolerance ±5% Number of Resistors 4 Number of Pins 8 Power Per Element 125mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount	Package	2012, Convex, Long Side Terminals
Resistance (Ohms) 22k Tolerance ±5% Number of Resistors 4 Number of Pins 8 Power Per Element 125mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount	Series	YC324
Tolerance $\pm 5\%$ Number of Resistors4Number of Pins8Power Per Element 125mW Temperature Coefficient $\pm 200 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 155 ^{\circ}\text{C}$ ApplicationsDDRAM, SDRAMMounting TypeSurface Mount	Circuit Type	Isolated
Number of Resistors4Number of Pins8Power Per Element125mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface Mount	Resistance (Ohms)	22k
Number of Pins8Power Per Element 125mW Temperature Coefficient $\pm 200 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 155 ^{\circ}\text{C}$ ApplicationsDDRAM, SDRAMMounting TypeSurface Mount	Tolerance	±5%
Power Per Element 125mW Temperature Coefficient $\pm 200 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 155 ^{\circ}\text{C}$ ApplicationsDDRAM, SDRAMMounting TypeSurface Mount	Number of Resistors	4
Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Applications DDRAM, SDRAM Mounting Type Surface Mount	Number of Pins	8
Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount	Power Per Element	125mW
Applications DDRAM, SDRAM Mounting Type Surface Mount	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount	Operating Temperature	-55°C ~ 155°C
	Applications	DDRAM, SDRAM
Package / Case 2012 Convey Long Side Terminals	Mounting Type	Surface Mount
t dekage / Case 2012, Convex, Long Side Terminars	Package / Case	2012, Convex, Long Side Terminals
Supplier Device Package -	Supplier Device Package	-
Size / Dimension 0.200" L x 0.126" W (5.08mm x 3.20mm)	Size / Dimension	0.200" L x 0.126" W (5.08mm x 3.20mm)
Height - Seated (Max) 0.028" (0.70mm)	Height - Seated (Max)	0.028" (0.70mm)
Report errors?		Report errors?

YC324-JK-0722KL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

YC324-JK-0722KL Payment Methods





















YC324-JK-0722KL Shipping Methods













If you have any question about YC324-JK-0722KL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com