

YS1005A Information

Heisener.com

Part Number YS1005A

Manufacturer Cosel USA, Inc.

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC POWER SUPPLY

Package 5-DIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









YS1005A Specifications

Manufacturer Part Number YS1005A Manufacturer Cosel USA, Inc. Category Power Supplies - Board Mount AC DC Converters Package 5-DIP Module Series YS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)		
Category Power Supplies - Board Mount AC DC Converters Package 5-DIP Module Series YS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Manufacturer Part Number	YS1005A
Package 5-DIP Module Series YS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Manufacturer	Cosel USA, Inc.
Package 5-DIP Module Series YS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Category	Power Supplies - Board Mount
Series YS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Package	5-DIP Module
Number of Outputs 1 Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Series	YS
Voltage - Input 85 ~ 132 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 10W Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case Size / Dimension 5V Output 2	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency Mounting Type Through Hole Package / Case Size / Dimension - Output 4 - Current - Output (Max) 2A Power (Watts) 10W ITE (Commercial) For (With Derating) The (With Derating) Through Hole Size / Dimension - 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Voltage - Input	85 ~ 132 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case Size / Dimension - United the second of	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension -0°C (With Derating) Through Hole Size / Dimension -0°C (With Derating) Through Hole	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 10W ITE (Commercial) Poc \(\text{Vision} \) The package / Case 5-DIP Module 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Voltage - Output 4	-
Applications ITE (Commercial) Features DC Input Capable Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Current - Output (Max)	2A
Features DC Input Capable -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension DC Input Capable -10°C ~ 70°C (With Derating) 73% Through Hole 5-DIP Module 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Power (Watts)	10W
Operating Temperature -10°C ~ 70°C (With Derating) Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Applications	ITE (Commercial)
Efficiency 73% Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Features	DC Input Capable
Mounting Type Through Hole Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Package / Case 5-DIP Module Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Efficiency	73%
Size / Dimension 2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)	Mounting Type	Through Hole
	Package / Case	5-DIP Module
Report errors?	Size / Dimension	2.28" L x 1.77" W x 0.73" H (58.0mm x 45.0mm x 18.5mm)
		Report errors?

YS1005A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

YS1005A Payment Methods



















YS1005A Shipping Methods













If you have any question about YS1005A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com