

ZMS10015 Information

Part Number ZMS10015

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 80W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZMS10015 Specifications

Power Supplies - External/Internal (Off-Board) AC DC Converters			
Power Supplies - External/Internal (Off-Board) AC DC Converters	Manufacturer Part Number	ZMS10015	
AC DC Converters Package - Series ZMS100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.4A Power (Watts) 80W (100W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series ZMS100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.4A Power (Watts) 80W (100W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series ZMS100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.4A Power (Watts) 80W (100W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)		AC DC Converters	
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5.4APower (Watts)80W (100W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.4A Power (Watts) 80W (100W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Series	ZMS100	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.4A Power (Watts) 80W (100W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Type	Open Frame	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, Universal Input Mounting Type Size / Dimension 15V 15V 15V 16V 16V 16V 16V 16V	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output 3 - Chassis Mount - Current - Output 4 - Current - Output (Max) - Commercial), Medical - Comm	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output 4 - Current - Output 4 - Current - Output (Max) - Commercial), Medical 4kV (4000V) - Commercial), Medical 4kV (4000V) - Commercial), Medical - Commercial), Medi	Voltage - Output 1	15V	
Voltage - Output 4 Current - Output (Max) 5.4A Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension -20°C × 20° W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Voltage - Output 2	-	
Current - Output (Max) 5.4A Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.4A 80W (100W Forced Air) ITE (Commercial), Medical 4kV (4000V) 87% Cyclote Air Adjustable Output Chasting Chasting 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 80W (100W Forced Air) ITE (Commercial), Medical 4kV (4000V) 87% Chassis Mount 4kV (4000V) 87% Chassis Mount 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Voltage - Output 4	-	
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Current - Output (Max)	5.4A	
Voltage - Isolation 4kV (4000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Power (Watts)	80W (100W Forced Air)	
Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Applications	ITE (Commercial), Medical	
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Chassis Mount 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Voltage - Isolation	4kV (4000V)	
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Efficiency	87%	
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Operating Temperature	-20°C ~ 70°C (With Derating)	
Size / Dimension 4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	Features	Adjustable Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errore?	Size / Dimension	4.00" L x 2.00" W x 1.25" H (101.6mm x 50.8mm x 31.8mm)	
Report chors:			Report errors?

ZMS10015 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZMS10015 Payment Methods



















ZMS10015 Shipping Methods













If you have any question about ZMS10015, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com