

## **ZPS4036 Information**



For Reference Only

Part Number ZPS4036

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 36V 40W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ZPS4036 Specifications**

Manufacturer Part Number         ZPS4036           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZP40           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	-	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZP40           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Manufacturer Part Number	ZPS4036
Package         -           Series         ZP40           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         ZP40           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         ZP40           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Package	-
Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Series	ZP40
Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         36V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.11A           Power (Watts)         40W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Sty (3000V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Mounting Type  Chassis Mount  Size / Dimension  36V  Output 2  - Current - Output (Max)  - Current - Output (Max)  1.11A  - Current - Output (Max)  40W  Chownercial)  Size / Tolke Commercial  Size / Dimension  Aut 2  - Chassis Mount  Chassis Mount  4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sirver (Watts) Applications Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  - Size / Dimension  ITE (Commercial)	Voltage - Output 1	36V
Voltage - Output 4  Current - Output (Max)  1.11A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  1.11A  4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 3	-
Power (Watts) 40W  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature 0°C ~ 70°C (With Derating)  Features DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency $87\%$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C (With Derating)$ FeaturesDC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension $4.00$ " L x $2.00$ " W x $1.20$ " H $(101.6mm x 50.8mm x 30.5mm)$	Current - Output (Max)	1.11A
Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature 0°C ~ 70°C (With Derating)  Features DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Power (Watts)	40W
Efficiency 87%  Operating Temperature 0°C ~ 70°C (With Derating)  Features DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Applications	ITE (Commercial)
Operating Temperature  0°C ~ 70°C (With Derating)  DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Efficiency	87%
Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Features	DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)
		Report errors?

### **ZPS4036 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ZPS4036 Payment Methods**





















## **ZPS4036 Shipping Methods**













If you have any question about ZPS4036, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com