

ZRT100GC2TC

ZRT100GC2TC Information

www.heisener.com	 ZRT100GC2TC Diodes Incorporated Integrated Circuits (ICs) PMIC - Voltage Reference IC VREF SHUNT 9.8V SOT223 TO-261-4, TO-261AA For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ZRT100GC2TC Specifications

Manufacturer Part NumberZRT100GC2TCManufacturerDiodes IncorporatedCategoryIntegrated Circuits (ICs)PackagePMIC - Voltage ReferencePackageTO-261-4, TO-261AASeries-Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)9.8VVoltage - Output (Max)-Current - OutputSinpanceTolerance2%Noise - Oltput ZoSinpanceNoise - Oltput ZoSinpanceVoltage - Input ResourceSinpanceCurrent - OutputSinpanceSolerance2%Current Supply-Noise - Infly ConflySinpanceCurrent Supply-Current - Supply-Current - Supply-Current - SupplySuface MonutPackage / CaseSurface MonutSuppler Device PackageSurface MonutSurface PackageSurface MonutSuppler Device PackageSurface Suppler Confly		
CategoryIntegrated Circuits (ICs)PackagePMIC - Voltage ReferencePackageTO-261-4, TO-261AASeries-Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)9.8VVoltage - Output (Max)-Current - Output30mATolerance±2%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz50µVp-pNoise - 10Hz to 10kHz-Voltage - Input-Qurrent - Supply-Qurrent - Supply-Qurrent - Cathode150µAOperating Temperature-Mounting Type-Sufface Mount-Package / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Manufacturer Part Number	ZRT100GC2TC
PMIC - Voltage ReferencePackageTO-261-4, TO-261AASeries-Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)9.8VVoltage - Output (Max)-Current - Output30mATolerance±2%Temperature Coefficient50µVp-pNoise - 0.1Hz to 10Hz-Voltage - Input-Voltage - Input150µVp-pNoise - 10Hz to 10kHz-Outrent - Supply-Outrent - Supply-Outrent - Cathode150µAOutring TypeSurface MountPortaing TypeSurface MountPackage / CaseTO-2614, TO-261AASupplier Device PackageSOT-223	Manufacturer	Diodes Incorporated
PackageTO-261-4, TO-261AASeries-Referenc TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)9.8VVoltage - Output (Max)-Current - Output30mATolerance2%Tomperature Coefficient50pm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10KHZ-Voltage - Input-Current - Supply-Current - Cathode150µAOperating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSUT-223	Category	Integrated Circuits (ICs)
Series-Referece TypeShuntOutput TypeFixedVoltage Output (Min/Fixed)9.8VVoltage Output (Max)-Current - Output30mATolerance±2%Tomperature Coefficient50pm/°CNoise - 0.1Hz to 10Hz50µVp-pNoise - 10Hz to 10Hz-Voltage Input-Current - Supply-Current - Cathode150µAOperating TemperatureSor C(TA)Mounting TypeSur GacuSuppler Device PackageSOT-223		PMIC - Voltage Reference
Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)9.8VVoltage - Output (Max)-Current - Output (Max)30mACurrent - Output42%Tolerance50pm/°CNoise - O.I Hz to 10Hz50µVp-pNoise - I Oltzt to 10Hz-Voltage - Input-Current - Supply-Current - Supply150µAOperating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-2614, TO-261AASupplier Device PackageSUT-223	Package	TO-261-4, TO-261AA
Output Type Fixed Voltage - Output (Min/Fixed) 9.8V Voltage - Output (Max) - Current - Output 30mA Tolerance ±2% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 50µVp-p Noise - 10Hz to 10KHZ - Voltage - Input - Qurrent - Supply - Qurrent - Cathode 150µA Operating Temperature 440°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case SOT-223	Series	-
Voltage - Output (Min/Fixed)9.8VVoltage - Output (Max)-Current - Output30mATolerance±2%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz50µVp-pNoise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode150µAOperating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSUT-223	Reference Type	Shunt
Voltage - Output (Max)-Current - Output30mATolerance±2%Temperature Coefficient50pm/°CNoise - 0.1Hz to 10Hz50µVp-pNoise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode150µAOperating Temperature40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Output Type	Fixed
Current - Output30mATolerance±2%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz50μVp-pNoise - 10Hz to 10KHz-Voltage - Input-Current - Supply-Current - Cathode150μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Voltage - Output (Min/Fixed)	9.8V
Tolerance ±2% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 50µVp-p Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 150µA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-261-4, TO-261AA	Voltage - Output (Max)	-
Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz50μVp-pNoise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode150μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Current - Output	30mA
Noise - 0.1Hz to 10Hz50μVp-pNoise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode150μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Tolerance	±2%
Noise - 10Hz to 10kHz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode150μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Temperature Coefficient	50ppm/°C
Voltage - Input-Current - Supply-Current - Cathode150μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Noise - 0.1Hz to 10Hz	50µVp-p
Current - Supply-Current - Cathode150μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Noise - 10Hz to 10kHz	-
Current - Cathode150µAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Voltage - Input	-
Operating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Current - Supply	-
Mounting TypeSurface MountPackage / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Current - Cathode	150μΑ
Package / CaseTO-261-4, TO-261AASupplier Device PackageSOT-223	Operating Temperature	-40°C ~ 85°C (TA)
Supplier Device Package SOT-223	Mounting Type	Surface Mount
	Package / Case	TO-261-4, TO-261AA
Report errors?	Supplier Device Package	SOT-223
		Report errors?

ZRT100GC2TC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ZRT100GC2TC Payment Methods



ZRT100GC2TC Shipping Methods



If you have any question about ZRT100GC2TC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com