

ZTB200D

a Quote

ZTB200D Information

		Part Number	ZTB200D	
		Manufacturer	ECS Inc.	
	www.stillbennie.com	Category	Crystals, Oscillators, Resonators Resonators	- 200
		Description	CER RES 200.0000KHZ T/H	15523
		Package	Radial, Box - 2 Lead, 10.00mm Pitch	
			For the pricing/inventory/lead time, please contact us	
	For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ZTB200D Specifications

Manufacturer ECS Inc. Category Crystals, Oscillators, Resonators Resonators Resonators Package Radial, Box - 2 Lead, 10.00mm Pitch Series ZTB Type Ceramic Frequency 200kHz Frequency Stability ±0.3% Frequency Tolerance ±1kHz Capacitance - Impedance - Operating Temperature -20°C ~ 80°C Mounting Type Radia, Box - 2 Lead, 10.00mm Pitch Servery Strauge Size / Dimension Strauge		
CategoryCrystals, Oscillators, ResonatorsResonatorsPackageRadial, Box - 2 Lead, 10.00mm PitchSeriesZTBTypeCeramicFrequency200kHzFrequency Stability40.3%Frequency Tolerance= ltkHzCapacitance-Capacitance-Operating Temperature-0°C ~ 80°CMounting TypeThrough HolePackage / CaseScillat Box - 2 Lead, 10.00mm PitchBight0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Manufacturer Part Number	ZTB200D
ResonatorsPackageRadial, Box - 2 Lead, 10.00mm PitchSeriesZTBTypeCeramicFrequency200kHzFrequency Stability±0.3%Frequency Tolerance±1kHzFrequency Tolerance-Capacitance-Operating Temperature-0°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchBise / Dimension0.579" (14.70mm)	Manufacturer	ECS Inc.
PackageRadial, Box - 2 Lead, 10.00mm PitchSeriesZTBTypeCeramicFrequency200kHzFrequency Stability±0.3%Frequency Tolerance±1kHzFrequency Colerance-Capacitance-Impedance-Operating Temperature20°C ~ 80°CMounting TypeThrough HolePackage / CaseStail, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Category	Crystals, Oscillators, Resonators
Series ZTB Series Ceranic Frequency 200kHz Frequency Stability ±0.3% Frequency Tolerance ±1kHz Frequency Tolerance - Capacitance - Capacitance - Operating Temperature - Mounting Type -20°C ~ 80°C Package / Case Radial, Box - 2 Lead, 10.00mm Pitch Size / Dimension 0.531" L x 0.150" W (13.50mm x 3.80mm) Height 0.579" (14.70mm)		Resonators
TypeCeramicFrequency200kHzFrequency Stability±0.3%Frequency Tolerance±1kHzFrequency Tolerance-Capacitance-Impedance-Operating Temperature-0°C ~ 80°CMounting TypeFridugh HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchBight0.579" (14.70mm)	Package	Radial, Box - 2 Lead, 10.00mm Pitch
Frequency200kHzFrequency Stability±0.3%Frequency Tolerance±1kHzFeatures-Capacitance-Impedance-Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Series	ZTB
Frequency Stability±0.3%Frequency Tolerance±1kHzFeatures-Capacitance-Impedance-Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.579" (14.70mm)	Туре	Ceramic
Frequency Tolerance±1kHzFeatures-Capacitance-Impedance-Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Frequency	200kHz
Features-Capacitance-Impedance-Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Frequency Stability	$\pm 0.3\%$
Capacitance-Impedance-Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Frequency Tolerance	±1kHz
Impedance-Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Features	-
Operating Temperature-20°C ~ 80°CMounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Capacitance	-
Mounting TypeThrough HolePackage / CaseRadial, Box - 2 Lead, 10.00mm PitchSize / Dimension0.531" L x 0.150" W (13.50mm x 3.80mm)Height0.579" (14.70mm)	Impedance	-
Package / Case Radial, Box - 2 Lead, 10.00mm Pitch Size / Dimension 0.531" L x 0.150" W (13.50mm x 3.80mm) Height 0.579" (14.70mm)	Operating Temperature	-20°C ~ 80°C
Size / Dimension 0.531" L x 0.150" W (13.50mm x 3.80mm) Height 0.579" (14.70mm)	Mounting Type	Through Hole
Height 0.579" (14.70mm)	Package / Case	Radial, Box - 2 Lead, 10.00mm Pitch
	Size / Dimension	0.531" L x 0.150" W (13.50mm x 3.80mm)
Report errors?	Height	0.579" (14.70mm)
		Report errors?

ZTB200D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ZTB200D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com