

ZWS100AF3/J

Quote

ZWS100AF3/J Information

		ZWS100AF3/J	
A Heisener.com	Category	TDK-Lambda Americas Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters	- 11.Sec - 2016
Gittal service starts then	Description Package	AC/DC CONVERTER 3.3V 100W	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Q

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ZWS100AF3/J Specifications

Manufacturer Part NumberZWS100AF3/IManufacturerTDK-Lambda Americas Inc.CategoryPower Supplies - External/Internal (Off-Board)ACDC ConvertersACDC ConvertersPackage-SeriesZWS-AFTypeEnclosedNumber of Outputs1Voltage - InputS5 > 265 > XGCVoltage - Output 13.3VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Solation-Voltage - Solation-Voltage - Solation-Voltage - Solation-Voltage - Output - Contro Civith Derating, PCC, Universal InputVoltage - Output - Contro Civith Derating, PCC, Universal InputVoltage - Output - Contro Civith Derating, PCC, Universal InputVoltage - Output - Contro Civith Derating, PCC, Universal InputVoltage - Dimension-<	-			
CategoryPower Supplies - External/Internal (Off-Board)Ac DC ConvertersPackage-SeriesZWS-AFTypeEnclosedNumber of Outputs1Voltage - InputS5 ~ 265 VACVoltage - Output 133VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Soltation-Voltage - Isolation-Voltage - Isolation	Manufacturer Part Number	ZWS100AF3/J		
AC DC Converters Package - Series ZWS-AF Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation ID6W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 69% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Sasis Mount Size / Dimension	Manufacturer	TDK-Lambda Americas Inc.		
Package-SeriesZWS-AFTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 13.3VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4Output -Voltage - Output 4-Voltage - Output 4Output -Voltage - Output 4Output -Voltage - Output 4-Voltage - Output 4Output -Voltage - Output 500WApplicationsITE (commercial)Voltage - Isolation3kV (3000V)Efficiency0%Operating Temperature-Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting Type8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series ZWS-AF Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 Output - Output 4 Voltage - Output 4 - Voltage - Output 5 Output - Output 4 Voltage - Output 4 - Voltage - Solation TE (Commercial) Voltage - Isolation StV (3000V) Efficiency 6% Operating Temperature - Voltage - Solation - Features Adjustable Output, DCI Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount		AC DC Converters		
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 13.3VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 404Power (Wats)100WPower (Wats)1FE (Commercial)Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting Type6,34" L x 2.44" W x 1.38" H (222.0mm x 63.0mm)	Package	-		
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 69% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chasis Mount Size / Dinension 8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Series	ZWS-AF		
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 69% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.44" W x 1.38" H (222.0mm x 35.0mm)	Туре	Enclosed		
Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 69% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type 8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Number of Outputs	1		
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 69% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Krasis Mount Size / Dimension 8.74" L x 2.44" W x 1.38" H (222.0mm x 35.0mm)	Voltage - Input	85 ~ 265 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)20APower (Watts)100WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Voltage - Output 1	3.3V		
Voltage - Output 4-Current - Output (Max)20APower (Watts)100WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Voltage - Output 2	-		
Current - Output (Max)20APower (Watts)100WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Voltage - Output 3	-		
Power (Watts)100WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Current - Output (Max)	20A		
Voltage - Isolation3kV (3000V)Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Power (Watts)	100W		
Efficiency69%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Applications	ITE (Commercial)		
Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Efficiency	69%		
Mounting TypeChassis MountSize / Dimension8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)		
Size / Dimension 8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)	Features	Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	8.74" L x 2.44" W x 1.38" H (222.0mm x 62.0mm x 35.0mm)		
			Report errors?	

ZWS100AF3/J Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS100AF3/J Payment Methods



ZWS100AF3/J Shipping Methods



If you have any question about ZWS100AF3/J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com