



ZWS10B15 Information

Part Number ZWS10B15

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 10W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZWS10B15 Specifications

Manufacturer ZWS10B15 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 700mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	•		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 700mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Manufacturer Part Number	ZWS10B15	
Package Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Siky (3000V) Efficiency Say Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Manufacturer	TDK-Lambda Americas Inc.	
Package-SeriesZWS10BTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)700mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis Mount	Category	Power Supplies - External/Internal (Off-Board)	
SeriesZWS10BTypeOpen FrameNumber of Outputs1Voltage - Input $85 \sim 265 \text{ VAC}$ Voltage - Output 1 15V Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max) 700mA Power (Watts) 10W ApplicationsITE (Commercial)Voltage - Isolation $3\text{kV} (3000\text{V})$ Efficiency 83% Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C} (\text{With Derating})$ FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis Mount		AC DC Converters	
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)700mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis Mount	Package	-	
Number of Outputs Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Series	ZWS10B	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 700mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Type	Open Frame	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Voltage - Output 1	15V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Voltage - Output 2	-	
Current - Output (Max) 700mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Current - Output (Max)	700mA	
Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Power (Watts)	10W	
Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount	Efficiency	83%	
Mounting Type Chassis Mount	Operating Temperature	-10°C ~ 70°C (With Derating)	
	Features	Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input	
	Mounting Type	Chassis Mount	
Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Size / Dimension	4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	
Report errors?			Report errors?

ZWS10B15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS10B15 Payment Methods



















ZWS10B15 Shipping Methods













If you have any question about ZWS10B15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com