

ZWS10B24 Information

For Reference Only

Part Number ZWS10B24

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 10W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZWS10B24 Specifications

Manufacturer Part Number ZWS10B24 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	•		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Manufacturer Part Number	ZWS10B24	
Package - Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series ZWS10B Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Package	-	
Number of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)500mAPower (Watts)10WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency84%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Series	ZWS10B	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Type	Open Frame	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Voltage - Isolation ITE (Commercial) Voltage - Isolation Site / Operating Temperature Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Size / Dimension 24V Voltage - Output 2	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Voltage - Output 1	24V	
Voltage - Output 4 Current - Output (Max) 500mA Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Voltage - Output 2	-	
Current - Output (Max) 500mA Power (Watts) 10W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Current - Output (Max)	500mA	
Voltage - Isolation 3kV (3000V) Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Power (Watts)	10W	
Efficiency 84% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Efficiency	84%	
Mounting Type Chassis Mount Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Operating Temperature	-10°C ~ 70°C (With Derating)	
Size / Dimension 4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	Features	Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	4.14" L x 1.97" W x 0.83" H (105.1mm x 50.0mm x 21.0mm)	
			Report errors?

ZWS10B24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS10B24 Payment Methods



















ZWS10B24 Shipping Methods













If you have any question about ZWS10B24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com