



# **ZWS300BAF24/L Information**

Heisener.com

Part Number ZWS300BAF24/L

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

**AC DC Converters** 

**Description** AC/DC CONVERTER 24V 300W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ZWS300BAF24/L Specifications**

Manufacturer Part Number         ZWS300BAF24/L           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZWS300BAF           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.5A           Power (Watts)         300W (336W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         88%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZWS300BAF           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.5A           Power (Watts)         300W (336W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         88%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Manufacturer Part Number	ZWS300BAF24/L	
Package         -           Series         ZWS300BAF           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.5A           Power (Watts)         300W (336W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         88%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package         -           Series         ZWS300BAF           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.5A           Power (Watts)         300W (336W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         88%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         ZWS300BAF           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.5A           Power (Watts)         300W (336W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         88%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)		AC DC Converters	
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12.5A           Power (Watts)         300W (336W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         88%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Package	-	
Number of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.5APower (Watts)300W (336W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Series	ZWS300BAF	
Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.5APower (Watts)300W (336W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Type	Open Frame	
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  24V  24V  24V  24V  24V  24V  24V  25V  26  27  28  28  28  28  28  28  28  28  28	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  88%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Voltage - Output 1	24V	
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  88%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Voltage - Output 2	-	
Current - Output (Max)  Power (Watts)  300W (336W Forced Air)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  88%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Voltage - Output 3	-	
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  88%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 88%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Current - Output (Max)	12.5A	
Voltage - Isolation 3kV (3000V)  Efficiency 88%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Power (Watts)	300W (336W Forced Air)	
Efficiency 88%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Applications	ITE (Commercial)	
Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Efficiency	88%	
Mounting Type Chassis Mount Size / Dimension 7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Operating Temperature	-10°C ~ 70°C (With Derating)	
Size / Dimension 7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	Features	Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	7.09" L x 3.31" W x 1.65" H (180.0mm x 84.0mm x 42.0mm)	
			Report errors?

#### **ZWS300BAF24/L Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ZWS300BAF24/L Payment Methods



















## ZWS300BAF24/L Shipping Methods













If you have any question about ZWS300BAF24/L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com