

ZWS3012/A Information

Heisener.com

Part Number ZWS3012/A

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 30W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZWS3012/A Specifications

Manufacturer Part Number ZWS3012/A Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Manufacturer Part Number	ZWS3012/A
Package - Series ZWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series ZWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ZWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Series	ZWS
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Type	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sty (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension Size / Dimension Size / Dimension Current - Output (Max)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Capable (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 2.5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 2	-
Current - Output (Max) 2.5A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 77% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension 5.24 " L x 2.17 " W x 1.02 " H $(133.0 \text{mm x} 55.1 \text{mm x} 25.9 \text{mm})$	Current - Output (Max)	2.5A
Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Power (Watts)	30W
Efficiency 77% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Efficiency	77%
Mounting Type Chassis Mount Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)
		Report errors?

ZWS3012/A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS3012/A Payment Methods

































If you have any question about ZWS3012/A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com