



### **ZWS303/JA Information**

Heisener.com

Part Number ZWS303/JA

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

**AC DC Converters** 

**Description** AC/DC CONVERTER 3V 30W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ZWS303/JA Specifications**

Manufacturer Part Number         ZWS303/JA           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZWS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZWS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Manufacturer Part Number	ZWS303/JA
Package         -           Series         ZWS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         ZWS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         ZWS           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 13VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency70%Operating Temperature-10°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Package	-
Number of Outputs       1         Voltage - Input       85 ~ 265 VAC         Voltage - Output 1       3V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       6A         Power (Watts)       30W         Applications       ITE (Commercial)         Voltage - Isolation       3kV (3000V)         Efficiency       70%         Operating Temperature       -10°C ~ 60°C (With Derating)         Features       Adjustable Output, DC Input Capable, Universal Input         Mounting Type       Chassis Mount         Size / Dimension       5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Series	ZWS
Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         70%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Type	Enclosed
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  3V  - Size / Dimension  3V  - Size / Output 2  - Current - Output (Max)  - Current - Output (Max)  6A  - Current - Output (Max)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  -  Voltage - Output 4  -  Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  Size / Dimension  - Output (Max)  - Current - Output (Max)  6A  - Output (Max)  6A  ITE (Commercial)  30W  ITE (Commercial)  3kV (3000V)  6A  Commercial)  Size / Dimension  - Ooc - 60°C (With Derating)  Chassis Mount  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 1	3V
Voltage - Output 4  Current - Output (Max)  6A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  70%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  30W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  70%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  70%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Output 4	-
Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  70%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Current - Output (Max)	6A
Voltage - Isolation  3kV (3000V)  Efficiency  70%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Power (Watts)	30W
Efficiency 70%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Applications	ITE (Commercial)
Operating Temperature  -10°C ~ 60°C (With Derating)  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Efficiency	70%
Mounting Type Chassis Mount  Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.24" L x 2.17" W x 1.02" H (133.0mm x 55.1mm x 25.9mm)
		Report errors?

#### **ZWS303/JA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ZWS303/JA Payment Methods**



















# **ZWS303/JA Shipping Methods**













If you have any question about ZWS303/JA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com